





TEST REPORT

Reference No	:	WTF25X06163965Y
Applicant	*:	Mid Ocean Brands B.V.

Address.....: Unit 711- 716, 7/F., Tower A, 83 King Lam Street, Cheung Sha Wan,

Kowloon, Hong Kong.

Manufacturer: 114768

Address.....: :---

Product Name.....: TWS earbuds

Model No.....: MO2079

Test specification.....: EN 50332-2:2013: Sound system equipment: Headphones and

earphones associated with personal music players

- Maximum sound pressure level measurement methodology

Part 2: Matching of sets with headphones if either or both are offered separately, or are offered as one package equipment but with standardized connectors between the two allowing to combine components of different manufacturers or different design

Date of Receipt sample..... : 2025-06-30

Date of Test.....: 2025-07-01 to 2025-07-02

Date of Issue..... : 2025-07-02

Test Report Form No......: WTX EN50332 2 2013A

Test Result.....: Pass

Remarks

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel:+86-755-33663308 Fax:+86-755-33663309 Email: sem@waltek.com.cn

Tested by:

kevin Ye

Kevin Ye / Project Engineer

Approved by:

Harvid Wei / Manager



Test item description	TWS earbuds

Trademark: ____

Model and/or type reference MO2079

Rating(s).....

1000	
Test Laboratory	Waltek Testing Group (Shenzhen) Co., Ltd.
Address	1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

General product information:

The sample(s) tested complies with the requirements of EN 50332-2: 2013.

Model Differences:

Main test models: MO2079

Summary of testing:

All tests had been assessed for safety with respect to the above test specifications and found to comply with the requirements of the standards.



Test case verdicts
Test case does not apply to the test object : N(N/A)
Test item does meet the requirement: P(Pass)
Test item does not meet the requirement: F(Fail)
General remarks
The test result presented in this report relate only to the object(s) tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.
The report would be invalid without specific stamp for test institute or the authority. The report would be invalid without the signatures of reporter and reviewer. "(see Enclosure #)" refers to additional information appended to the report. "(see appended table)" refers to a table appended to the report.
Remark:
Whether parts of tests for the product have been subcontracted to other labs: ☐ Yes ☐ No
If Yes, list the related test items and lab information: Test items:
Lab information:



EN 50332-2: 2013			
Clause	Requirement – Test	Result - Remark	Verdict

4	Basic conditions for specifications and measurements (For basic conditions on measurements of the maximum sound pressure level, reference is made to EN 50332-1.)	
4.1	General description	Р
WAL TE	The sound pressure level produced by headphones or earphones can be measured by subjective methods or by objective methods.	Р
INLIEK.	The reference method for evaluating the sound pressured level emitted by earphones is a psycho acoustic method known as "equal loudness" (EN60268-7)	Р
4.2	Measuring principle	Julia Bill
y writ	The standard is based on the use of a Head and Torso Simulator (HATS) in accordance with IEC 60318-7	P
WALTER ALTER	The sound pressure level measured by the ear simulator microphone represents the pressure found at eardrum level and differs from that of the free field pressure by the HATS transfer function	P

5	Player characteristics and methods of measurement	
5.1	Maximum output voltage Vm	* Jet Jet Niet
5.2	Method of measurement and conditions	N_
5.2.1	Input signal	MITTER MILIE MILIN W
LIEK W	Actual musical signals are continuously fluctuating in both amplitude and spectral contents and thus cannot be used as test signals	NUTER WALLER WALLER
EK WILT	The test signal must therefore be a stationary wide-band signal, the spectral content of which is representative of the musical signals.	et unifer un en with
unitek unitek	The test signal used to determine the maximum sound pressure level of headphones shall be programme simulation noise, as defined in HD 483.1 S2.	while while with wh
5.2.2	Operating conditions	THE STEEL STEEL NOW!
	- By a established power supply	N +
" Mery	- tolerance of nominal supply voltage	white will will
MITER	- All controls are adjusted to maximum sound pressure level	nitet mitet un N'

Waltek Testing Group (Shenzhen) Co., Ltd. http://www.waltek.com.cn



EN 50332-2: 2013				
Clause	Requirement – Test	Result - Remark	Verdict	
zet-	- load of player output	The The Cat	N-	
5.2.3	Method of measurement for analogue audio outputs	MILLE MILLE MILL	N	
iek vile	The measuring equipment shall conform to: - EN 61672-1, class 1 for (sound level meters); - EN61260, class 1 for (1/3 octave analysers).	united white white w	LET N	
MALTER	The maximum output voltage Vm shall be defined as unweithted r.m.s. voltage at the load, using an averaging time of 30 s or more.	A WILE MILES MATER	- Wall Wat	
5.2.4	Method of measurement for digital audio outputs	A St St	N N	
itek mi	The maximum output level Lm shall be defined as average of digital signal, using an averaging time of 30 s or more.	Whit will will w	ETEK WITTER SINT	
K NUTER	The digital input test signal is defined in EN 50332-1 as -10 dBFS.	et jet lijet sli	et Net	

6	Headphone/Earphone characteristics and methods of measurement	
6.1	Measuring equipment	
LEK MUT	The measuring equipment shall be in accordance with EN 61672-1when connected with a HATS microphone.	A THE STATE OF THE
6.2	Simulated programme signal characteristic voltage	MALER WALLER WEEK
6.3	Method of measurement arrangement and conditions	LIET MITER MITER AND
6.3.1	Input signal	A A P
et de	- is program simulation noise as defined in HD 483.1 S2	P
"In	- according part 1, subclause 5.1	me me h
6.3.2	Source impedance of analogue input devices	THE NEW PERSON
	- output impedance of the test signal source	Р
6.3.3	Acoustical measurement method	IT WE PUT
6.3.4	Headphones / earphones fit	+ At At P
*	- Position correctly for measuring maximum sound pressure	P P
Me	- the manufacturer's instruction for correct use	Mur Mu Mb
6.3.5	Measure of evaluation	Alt All AP I



EN 50332-2: 2013				
Clause	Requirement – Test	Result - Remark	Verdict	
, et	- part 1, subclause 6.4	in an an	P	
are a	- sound pressure level reaches 94 dB SPL	TE MITER MATTER WALTER	The All N	

WATERER



Table 2 - Classification of the characteristics to be specified

Subclause	Characteristics	Products	
5.1	Maximum output voltage	Player	
6.1	Wide band characteristic voltage	Headphones	

Measuring result:

5.1	Measuring result		WELL WILL NOTE !	
	SPL (dB)	Vmax (mV)	Criterion request(mV)	
Left side	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	TER MITER MILE MILE MILE MI	nur mu	
Right side	WILL MULL MULL MULL	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	LIER HIER	

6.3.5	Measuring result (SPL) (Part 1, 6.4) (Bluetooth mode)				P
m. n	Measurement No.1	Measurement No.2	Measurement No.3	Measurement No.4	Measurement No.5
Left side	78.76	78.79	78.80	78.82	78.80
Right side	80.93	80.87	80.95	80.96	80.95
Average	Left side: 78.79	Alas	Right side: 80.94	NALL W	Vr. 215 2

6.3.5	Measuring result (WBCV)	THE MITTER WALLEN	
	SPL (dB)	VwBCV (mV)	Criterion request(mV)
Left side	94	ill white white white	≥75
Right side	94	at the set of	≥75

Waltek Testing Group (Shenzhen) Co., Ltd. http://www.waltek.com.cn



Photo Documentation

Model: MO2079



Photo 1



Photo 2



Photo Documentation



Photo 3



Photo 4

===== End of Report =====