

EMC Test Report

Report No.: AGC05443240944EE01

PRODUCT DESIGNATION: USB portable fan with stand

BRAND NAME : N/A

MODEL NAME : MO2490

APPLICANT: MID OCEAN BRANDS B.V.

DATE OF ISSUE : Oct. 08, 2024

EN IEC 55014-1:2021

STANDARD(S) : EN IEC 55014-2:2021 : EN IEC 61000 3 3:2010 (A

EN IEC 61000-3-2:2019/A1:2021 EN 61000-3-3:2013/A2:2021

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 50

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	1	Oct. 08, 2024	Valid	Initial release







Table of contents

1. Genera	al information	5
2. Descri	ption of Test Configuration	6
2.1.	Technical Description of Product	6
2.2.	Description of Support Equipment	6
2.3.	Description of Test Modes	6
3. Summ	ary of Measurement Results and Uncertainty	7
3.1.	Test Specifications	7
3.2.	Description of Measurement Results	7
3.3.	Description of Measurement Uncertainty	9
4. Test Fa	acility	10
5. Measu	rement of Conducted Emissions from the AC Mains Power Ports	11
5.1.	Requirements	11
5.2.	Block Diagram of Test Setup	12
5.3.	Equipment Details	13
5.4.	Configuration of the EUT and method of measurement	13
5.5.	Test Summary	14
6. Measu	rement of Radiated Emissions at Frequencies up to 1 GHz	16
6.1.	Requirements	16
6.2.	Block Diagram of Test Setup	16
6.3.	Equipment Details	17
6.4.	Configuration of the EUT and method of measurement	17
6.5.	Test Summary	18
7. Measu	rement of Harmonic Current Emissions	20
7.1.	Requirements	20
7.2.	Block Diagram of Test Setup	21
7.3.	Equipment Details	21
7.4.	Configuration of the EUT and method of measurement	21
7.5.	Test Summary	22
8. Measu	rement of Voltage Fluctuations and Flicker	23
8.1.	Requirements	23
8.2.	Block Diagram of Test Setup	23
8.3.	Equipment Details	23
8.4.	Configuration of the EUT and method of measurement	24





	8.5.	Test Summary	24
9. M	easur	ement of Electrostatic discharge	25
	9.1.	Requirements	25
	9.2.	Block Diagram of Test Setup	25
	9.3.	Equipment Details	26
	9.4.	Configuration of the EUT and method of measurement	26
	9.5.	Test Summary	27
10. N	/leasu	rement of Radio-Frequency Electromagnetic Field	28
	10.1.	Requirements	28
	10.2.	Block Diagram of Test Setup	29
	10.3.	Equipment Details	30
	10.4.	Configuration of the EUT and method of measurement	30
	10.5.	Test Summary	31
11. N	<i>l</i> leasu	rement of Radio-frequency common mode	32
	11.1.	Requirements	32
	11.2.	Block Diagram of Test Setup	32
	11.3.	Equipment Details	33
	11.4.	Configuration of the EUT and method of measurement	33
	11.5.	Test Summary	34
12. N	/leasu	rement of Fast Transients	35
	12.1.	Requirements	35
	12.2.	Block Diagram of Test Setup	35
	12.3.	Equipment Details	36
	12.4.	Configuration of the EUT and method of measurement	36
	12.5.	Test Summary	37
13. N	/leasu	rement of Surges	38
	13.1.	Requirements	38
	13.2.	Block Diagram of Test Setup	38
	13.3.	Equipment Details	39
	13.4.	Configuration of the EUT and method of measurement	39
	13.5.	Test Summary	39
14. F	Photo	graphs of Test Setup	40
15. F	hoto	graphs of EUT	44



Report No.: AGC05443240944EE01 Page 5 of 50

1. General information

Applicant	MID OCEAN BRANDS B.V.
Address	7/F. Kings Tower , 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Manufacturer	MID OCEAN BRANDS B.V.
Address	7/F. Kings Tower , 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Factory	MID OCEAN BRANDS B.V.
Address	7/F. Kings Tower , 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Product Designation	USB portable fan with stand
Brand Name	N/A
Test Model	MO2490
Series Model(s)	N/A
Difference Description	N/A
Deviation from Standard	No any deviation from the test method
Date of receipt of test item	Sep. 23, 2024
Date of Test	Sep. 23, 2024 to Oct. 08, 2024
Test Result	Pass
Test Report Form No	AGCER-EMC-GEN-V1
Note: The test results of th	is report relate only to the tested sample identified in this report.

Prepared By	Jouk Gai	
	Jack Gui (Project Engineer)	Oct. 08, 2024
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Oct. 08, 2024
Approved By	Max Zhang	
	Max Zhang (Authorized Officer)	Oct. 08, 2024




Page 6 of 50

2. Description of Test Configuration

2.1. Technical Description of Product

Categorization of Equipment	Category III equipment
Test arrangements of EUT	Table-top
Hardware Version	N/A
Software Version	N/A
Highest Internal Frequency	Less than 108MHz
EUT Input Rating	DC 5V by adapter or DC 3.7V by battery
Battery Information	DC 3.7V 2000mAh 7.4Wh

Connection Diagram of Host System



I/O Port Information (⋈ Applicable ☐ Not Applicable)

Port Type	Input/Output	Number	Cable Description
USB Type-C	In	1	0.25m unshielded

2.2. Description of Support Equipment

Device Type	Manufacturer	Model Name	Specifications	Data Cable	Power Cable
Adapter	Adapter Huawei HW-200440C00		-	-	

2.3. Description of Test Modes

No.	Test Mode Description	Worst
1	Normal operation mode with charging	
2	Normal operation mode	

Note: 1. Only worst mode data recorded in the test report.



Page 7 of 50

3. Summary of Measurement Results and Uncertainty

3.1. Test Specifications

EN IEC 55014-1:2021	Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 1: Emission
EN IEC 55014-2:2021	Electromagnetic compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 2: Immunity - Product family standard
EN IEC 61000-3-2:2019/A1:2021	Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current 16 A per phase)
EN 61000-3-3:2013/A2:2021	Electromagnetic compatibility (EMC) Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection

3.2. Description of Measurement Results

Test items	Test Standard(s)	Verdict
Conducted emissions from the AC mains power ports	EN IEC 55014-1	Pass
Radiated emissions at frequencies up to 1 GHz	EN IEC 55014-1	Pass
Harmonic current emissions	EN IEC 61000-3-2	Pass
Voltage fluctuations and flicker	EN 61000-3-3	Pass
Electrostatic discharge	IEC 61000-4-2°	Pass
Radio-frequency electromagnetic field	IEC 61000-4-3 a	Pass
Fast transients	IEC 61000-4-4 a	Pass
Surges	IEC 61000-4-5°	Pass
Radio-frequency common mode (Injected currents)	IEC 61000-4-6 a	Pass
Voltage dips and interruptions	IEC 61000-4-11 a	N/A
Niste.	•	

Note:

a. The applicable versions of the basic standards are defined in the standard which listed in the test specification.

b. N/A means not applicable.



Page 8 of 50

Performance table

	Performance Criteria for Immunity
Performance criterion A	The apparatus shall continue to operate as intended during the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.
Performance criterion B	The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. During the test, degradation of performance is allowed, however no change of actual operating state or stored data is allowed to persist after the test. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.
Performance criterion C	Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls, or by any operation specified in the instructions for use.



Page 9 of 50

3.3. Description of Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty	
Conducted emissions from the AC mains power ports	Uc = ±2.9 dB	
Radiated emissions at frequencies up to 1 GHz	Uc = ±3.9 dB	



Report No.: AGC05443240944EE01 Page 10 of 50

4. Test Facility

Laboratory name: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Laboratory Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laborat ories (CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This laboratory also meets the requirements of any additional program requirements in the Electrical field.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

CAB identifier: CN0063

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

VCCI Membership No.: 4112

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered in accordance with VCCI Council Rules.

VCCI Registration No. C-20098 for conducted emissions at AC main power ports

VCCI Registration No. T-20102 for conducted emissions at telecommunication ports

VCCI Registration No. R-20136 for radiated emissions below 1GHz

VCCI Registration No. G-20132 for radiated emissions above 1GHz



Page 11 of 50

5. Measurement of Conducted Emissions from the AC Mains Power Ports

5.1. Requirements

General limits for conducted emissions, low voltage AC mains port

Network device	Detector type/ bandwidth	Frequency Range (MHz)	Limits dB(µV)	Measurement specifications
	_	0.15 to 0.5	66 to 56	
	Quasi-peak/ 9kHz	0.5 to 5	56	Instrumentation: CISPR 16-1-1, Clauses 4, 5
AMN	OKI 12	5 to 30	60	and 7
AIVIN		0.15 to 0.5	59 to 46	Networks: CISPR 16-1-2, Clause 4
	Average/ 9kHz	0.5 to 5	46	Method: CISPR 16-2-1, Clause 7
		5 to 30	50	Set-up: CISPR 16-2-1, Clause 7

Note:


- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.5MHz.

Limits for the mains port of motor operated tools

Frequency		Tool	er of the motor	r only.)		
range	P ≤ 700	O W	700 W < P s	≤ 1 000 W	P > 10	00 W
1	2	3	4	5	6	7
MHz	Quasi-peak dB(µV)	Average dB(µV)	Quasi-peak dB(µV)	Average dB(µV)	Quasi-peak dB(µV)	Average dB(µV)
0.15 to 0.35	66 to 59	59 to 49	70 to 63	63 to 53	76 to 69	69 to 59
0.35 to 5	59	49	63	53	69	59
5 to 30	64	54	68	58	74	64


Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.35MHz.





5.2. Block Diagram of Test Setup





Page 13 of 50

5.3. Equipment Details

Measuring Instruments


Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	May 28, 2024	May 27, 2025
Artificial Mains Network	R&S	ESH2-Z5	100086	May 28, 2024	May 27, 2025
Attenuator	East sheep	LM-XX-6-5W	N/A	Jun. 09, 2023	Jun. 08, 2025

Measuring Software

Software Name	Manufacturer	Details
ES-K1	R&S	For EMC Measurement, Version 1.71

5.4. Configuration of the EUT and method of measurement


- The EUT was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, the EUT was placed on the top surface of a measurement table, 0.8 m high from the horizontal reference plane, and was positioned at a distance of 0.4 m away from the vertical reference plane. When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 10 cm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per CISPR 16-2-1. b.
- C. All I/O cables were positioned to simulate typical actual usage as per CISPR 16-2-1.
- The EMI receiver measured the emission levels emanating from the EUT into the AC Mains through an d. Artificial Mains Network (AMN) and an attenuator used on the front end of the EMI receiver. Testing included measurements on all live and neutral lines.
- The more description of the tests, the test methods, and the test set-ups are given in the applicable test e. standard.
- f. Record at least six highest emissions relative to the limits at each frequency of interest unless the emission is 10 dB or greater below the limit.
- g. A conducted emission is calculated by the following equation:
 - Measurement Level ($dB\mu V$) = Receiver reading ($dB\mu V$) + Tansd (dB)
 - Transd(dB)= AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
 - Margin= Limit-Level





5.5. Test Summary


Test Engineer	Carpe Lin	Temperature	22.6 ℃
Test Date	2024-10-08	Air Pressure	985 Mbar
Worst Mode	Mode 1	Relative Humidity	57.3 %
Verdict	Pass		




Frequency [MHz]	Level [dBµV]	Factor [dB]	Limit [dBµV]	Margin [dB]	Detector	Line
0.710000	32.5	6.2	56.0	23.5	QP	L1
0.778000	35.1	6.2	56.0	20.9	QP	L1
1.018000	32.6	6.2	56.0	23.4	QP	L1
1.150000	33.2	6.2	56.0	22.8	QP	L1
1.298000	32.9	6.2	56.0	23.1	QP	L1
1.342000	32.9	6.2	56.0	23.1	QP	L1
0.358000	26.8	6.1	49.6	22.8	AV	L1
0.778000	28.0	6.2	46.0	18.0	AV	L1
1.154000	26.2	6.2	46.0	19.8	AV	L1
2.122000	21.6	6.2	46.0	24.4	AV	L1
3.294000	18.1	6.3	46.0	27.9	AV	L1
4.918000	17.4	6.3	46.0	28.6	AV	L1

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/







Frequency [MHz]	Level [dBµV]	Factor [dB]	Limit [dBµV]	Margin [dB]	Detector	Line
0.470000	32.6	6.1	56.5	23.9	QP	N
0.582000	32.4	6.2	56.0	23.6	QP	N
0.986000	34.0	6.2	56.0	22.0	QP	N
1.126000	33.5	6.2	56.0	22.5	QP	N
1.334000	33.7	6.2	56.0	22.3	QP	N
1.486000	33.7	6.2	56.0	22.3	QP	N
0.342000	27.1	6.1	50.1	23.0	AV	N
0.554000	26.3	6.2	46.0	19.7	AV	N
1.382000	26.2	6.2	46.0	19.8	AV	N
2.130000	21.9	6.2	46.0	24.1	AV	N
5.450000	14.5	6.4	50.0	35.5	AV	N
27.042000	14.5	8.1	50.0	35.5	AV	N



Page 16 of 50

6. Measurement of Radiated Emissions at Frequencies up to 1 GHz


6.1. Requirements

Requirements for radiated emissions at frequencies up to 1 GHz at 3m distance

Test facility	Detector type/ bandwidth	Frequency Range (MHz)	Limits dB(µV/m)	Measurement specifications
04.0	Quasi-peak/	30 to 230	40	Instrumentation: CISPR 16-1-1, Clauses 4, 5 Antennas: CISPR 16-1-4, Clause 4.5
SAC	120kHz	230 to 1000	47	Test Site: CISPR 16-1-4, Clause 6 Method: CISPR 16-2-3, Clause 7.6

Note:

6.2. Block Diagram of Test Setup



^{1.} The lower limit shall apply at the transition frequency.



Page 17 of 50

6.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 01, 2024	Jan. 31, 2025
Antenna	SCHWARZBECK	VULB9168	D69250	May 11, 2023	May 10, 2025
Attenuator	Eastsheep	LM-XX-6-5W		Jun. 09, 2023	Jun. 08, 2025

Measuring Software

Software Name	Manufacturer	Details
EZ-EMC	FARA	For EMC Measurement, Version RA-03A

6.4. Configuration of the EUT and method of measurement


- a. The EUT was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, the EUT was placed on the top surface of a measurement table, 0.8 m high from the horizontal reference plane. When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 10 cm non-conductive covering to insulate the EUT from the ground plane.
- b. Support equipment, if needed, was placed as per CISPR 16-2-3.
- c. All I/O cables were positioned to simulate typical actual usage as per CISPR 16-2-3.
- d. The maximum receiving level of radiated emissions from the EUT was measured while the turntable was rotated from 0° to 360° and the antenna height was scanned between 1 m and 4 m. The cables were laid out to attain the maximum level of radiated emissions.
- e. The more description of the tests, the test methods, and the test set-ups are given in the applicable test standard.
- f. Record at least six highest emissions relative to the limits at each frequency of interest unless the emission is 10 dB or greater below the limit.
- g. A radiated emission is calculated by the following equation:
 - Measurement Level $dB(\mu V/m) = Receiver reading dB(\mu V) + Factor(dB/m)$
 - Factor(dB/m) = Antenna Factor(dB/m) + Cable Loss(dB)
 - Margin= Limit-Level




Report No.: AGC05443240944EE01 Page 18 of 50


6.5. Test Summary

Test Engineer	Alex Yang	Temperature	22.8 ℃
Test Date	2024-09-24	Air Pressure	985 Mbar
Worst Mode	Mode 1	Relative Humidity	59.7 %
Verdict	Pass		











Page 20 of 50

7. Measurement of Harmonic Current Emissions

7.1. Requirements

Applicable test standard(s): EN IEC 61000-3-2:2019/A1:2021

Limits of Harmonic Current Emissions

	Limits				
	Class A	Class A Class B Class C ^a		Class D	
Harmonic order h	Maximum permissible harmonic current (A)		Maximum permissible harmonic current expressed as a percentage of the input current at the fundamental frequency (%)	Maximum permissible harmonic current per watt (mA/W)	Maximum permissible harmonic current (A)
3	2.30	3.45	27 ^b	3.4	2.30
5	1.14	1.71	10	1.9	1.14
7	0.77	1.155	7	1.0	0.77
9	0.40	0.6	5	0.5	0.40
11	0.33	0.495	3	0.35	0.33
13	0.21	0.315	3	3.85/13	0.21
15≤ <i>h</i> ≤39(odd harmonics only)	2.25/h	3.375/h	3	3.85/h	2.25/h
2	1.08	1.62	2		
4	0.43	0.645			
6	0.30	0.45	Not applicable	Not applicable	Not applicable
8≤h≤40(even harmonics only)	1.84/h	2.76/h			

Note:

The application of limits had been as defined in the applicable test standard.


⁽a) For some Class C products, other emission limits apply.

⁽b) The limit is determined based on the assumption of modern lighting technologies having power factors of 0.90 or higher



Page 21 of 50

7.2. Block Diagram of Test Setup



7.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Conditioning Unit	Schaffner	CCN1000-1	72431	May 24, 2024	May 23, 2025
AC Source	Schaffner	NSG 1007	56825	May 24, 2024	May 23, 2025

Measuring Software

Software Name	Manufacturer	Details
CTS 4	AMETEK	For harmonics and flickers measurement, version 4.29.0

7.4. Configuration of the EUT and method of measurement

- The test shall be conducted according to the general requirements given in the applicable test standard.
 The test duration had been as defined in the applicable test standard.
- b. The measurement of harmonic currents shall be performed as follows:
 - for each harmonic order, measure the 1.5 s smoothed RMS harmonic current in each discrete Fourier transform (DFT) time window;
 - calculate the arithmetic average of the measured values from the DFT time windows, over the entire observation period.
- c. The value of the active input power to be used for the calculation of limits shall be determined as follows:
 - measure the 1.5 s smoothed active input power in each DFT time window;
 - determine the maximum of the measured values of active power from the DFT time windows over the entire duration of the test.



Page 22 of 50

d. The harmonic currents and the active input power shall be measured under the same test conditions but need not be measured simultaneously.

7.5. Test Summary

Equipment with a rated power less than or equal to 75W is deemed to fulfil all relevant requirements of this standard without testing.



Page 23 of 50

8. Measurement of Voltage Fluctuations and Flicker


8.1. Requirements

Applicable test standard(s): EN 61000-3-3:2013/A2:2021

Limits of Voltage Fluctuations and Flicker

Parameters	Definitions	Limits
T _{max}	the accumulated time value of $d(t)$ with a deviation exceeding 3.3 % during a single voltage change at the EUT terminals	≤500 ms
d _c	the maximum relative steady-state voltage change	≤3.3%
d _{max}	the maximum relative voltage change	⊠ ≤4% □ ≤6% □ ≤7%
$\boxtimes P_{st}$	short-term flicker severity	≤1.0
$\Box P_{lt}$	long-term flicker severity	≤0.65

8.2. Block Diagram of Test Setup



8.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Conditioning Unit	Schaffner	CCN1000-1	72431	May 24, 2024	May 23, 2025
AC Source	Schaffner	NSG 1007	56825	May 24, 2024	May 23, 2025

Measuring Software

Software Name	Manufacturer	Details	
CTS 4	AMETEK	For harmonics and flickers measurement, version 4.29.0	



Report No.: AGC05443240944EE01 Page 24 of 50

8.4. Configuration of the EUT and method of measurement


- a. The test shall be conducted according to the general requirements given in the applicable test standard.

 The test duration and test condition had been as defined in the applicable test standard.
- b. All types of voltage fluctuations would been assessed by direct measurement using a flicker meter which complies with the specification given in IEC 61000-4-15:2010.

8.5. Test Summary

Test Engineer	Jimu Lao	Temperature	23.4 ℃
Test Date	2024-09-25	Air Pressure	985 Mbar
Worst Mode	Mode 1	Relative Humidity	54.6 %
Verdict	Pass		

Parameters	Measurement Value	Limits
T _{max}	0	≤500 ms
d _c	0.00	≤3.3%
d _{max}	0.51	≤4%
P _{st}	0.344	≤1.0






9. Measurement of Electrostatic discharge

9.1. Requirements

Port	Enclosure	
Basic Standard	IEC 61000-4-2	
Test Level	±8.0 kV (Air Discharge) ±4.0 kV (Contact Discharge) ±4.0 kV (Indirect Discharge)	
Required Performance Criterion	В	
Time Between Each Discharge:	1 second	
Number of Discharge for Each Applied Voltage	10	

9.2. Block Diagram of Test Setup





Page 26 of 50

9.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
ESD Simulator	Schaffner	NSG 438	782	Nov. 13, 2023	Nov. 12, 2024

Measuring Software

Software Name Manufacturer		Details	

9.4. Configuration of the EUT and method of measurement

- a. Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- b. The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- c. The time interval between two successive single discharges was at least 1 second.
- d. The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the EUT.
- e. Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- f. Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were completed.
- g. At least ten single discharges (in the most sensitive polarity) were applied to the Horizontal Coupling Plane at points on each side of the EUT. The ESD generator was positioned vertically at a distance of 0.1 meters from the EUT with the discharge electrode touching the HCP.
- h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane in sufficiently different positions that the four faces of the EUT were completely illuminated. The VCP (dimensions 0.5m×0.5m) was placed vertically to and 0.1 meters from the EUT.
- i. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Report No.: AGC05443240944EE01 Page 27 of 50

9.5. Test Summary

Test Engineer	Carpe Lin	Temperature	22.7 ℃
Test Date	2024-09-26	Air Pressure	985 Mbar
Test Mode(s)	Mode 1/2	Relative Humidity	51.3 %
Verdict	Pass		

Voltage	Coupling	Observation	Performance
±4kV	Contact Discharge	N/A	N/A
±2KV, ±4kV, ±8kV	Air Discharge	No degradation of performance	A
±4kV	Indirect Discharge HCP	No degradation of performance	A
±4kV	Indirect Discharge VCP	No degradation of performance	А

Blue line: Air discharge





Note: Contact discharge point not found.



Page 28 of 50


10. Measurement of Radio-Frequency Electromagnetic Field

10.1. Requirements

Port	Enclosure
Basic Standard	IEC 61000-4-3
Required Performance Criterion	A
Test Level	3V/m with 80% AM. 1kHz Modulation at 80 to 1000MHz
Antenna polarization	Vertical and Horizontal
Step size increment ^a	1%
Dwell time b	≤5 seconds
Test Distance	3m
EUT position facing antenna	Front side, back side, left side and right side


Notes:

- a. Recognizing that a 1% step size is preferred, the frequency range can be swept incrementally with a step size not exceeding 4% of the previous frequency with a test level of twice the value of the specified test level in order to reduce the testing time for equipment requiring testing in multiple configurations and/or long cycle times.
- b. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to be able to respond. However, the dwell time shall not exceed 5 seconds at each of the frequencies during the scan. The time to exercise the EUT is not interpreted as a total time of a program or a cycle but related to the reaction time in case of failure of the EUT.





10.2. Block Diagram of Test Setup





Report No.: AGC05443240944EE01 Page 30 of 50

10.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Generator	Aglient	N5182A	MY50140530	Feb. 01, 2024	Jan. 31, 2025
Power Probe	R&S	URV5-Z4	100124	Mar. 24, 2023	Mar. 23, 2025
Power Meter	R&S	NRVD	8323781027	Mar. 24, 2023	Mar. 23, 2025
Directional coupler	Werlatone	C5571-10	99463	Feb. 01, 2024	Jan. 31, 2026
Power Amplifier	KALMUS	7100LC	04-02/17-06-001	Jul. 24, 2024	Jul. 23, 2025
Wideband Antenna	ETS	3142C	00060447		

Measuring Software

Software Name	Manufacturer	Details
TS+[JS35-RS]	Tonscend	For EMC measurement, version 2.0.1.8

10.4. Configuration of the EUT and method of measurement

- a. The Equipment Under Test (EUT) was positioned within the Uniform Field Area (UFA) on a supporting table, ensuring a 3-meter separation from the transmitting antenna. This setup aligns with the calibrated square area, guaranteeing field uniformity during testing. The supporting units were strategically located outside the UFA to avoid any potential interference. Nonetheless, the cables connected to the EUT were intentionally exposed to the precisely calibrated field within the UFA.
- b. Before testing, it will verify the proper operation of the test equipment/system. This verification will involve measuring the field strength at one point within the Uniform Field Area (UFA) at various frequencies.
- c. The test shall be performed according to the above requirements and block diagram which shall specify the test setup.
- d. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Page 31 of 50

10.5. Test Summary

Test Engineer	Alex Yang	Temperature	22.8 ℃
Test Date	2024-09-24	Air Pressure	985 Mbar
Test Mode(s)	Mode 1/2	Relative Humidity	59.7 %
Verdict	Pass		

Frequency	Exposed Side	Field Strength (V/m)	Observation	Performance
	Front		No degradation of performance	А
80MHz to 1GHz	Left	3V/m (rms)	No degradation of performance	А
OUMINZ TO TGINZ	Rear		No degradation of performance	А
	Right		No degradation of performance	А



Report No.: AGC05443240944EE01 Page 32 of 50

11. Measurement of Radio-frequency common mode


11.1. Requirements

Port	⊠AC mains power ports	signal, wired network and control ports ^a	☐ DC power ports ^a		
Basic Standard	IEC 61000-4-6				
Required Performance Criterion	А				
Test Level	3 V RMS (unmodulated), 80 % AM (1 kHz)	1 V RMS (unmodulated), 80 % AM (1 kHz)	1 V RMS (unmodulated), 80 % AM (1 kHz)		
Test Frequency	☑ 0.15 to 80 MHz ☐ 0.15 to 230 MHz				
Step size increment b	1%				
Dwell time °	≤5 seconds				

Notes:

- a. Applicable only to ports which, according to the manufacturer's specification, supports cable lengths greater than 3 m.
- b. Recognizing that a 1% step size is preferred, the frequency range can be swept incrementally with a step size not exceeding 4% of the previous frequency with a test level of twice the value of the specified test level in order to reduce the testing time for equipment requiring testing in multiple configurations and/or long cycle times.
- c. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to be able to respond. However, the dwell time shall not exceed 5 seconds at each of the frequencies during the scan. The time to exercise the EUT is not interpreted as a total time of a program or a cycle but related to the reaction time in case of failure of the EUT.

11.2. Block Diagram of Test Setup



Ground Reference Plane



Page 33 of 50

11.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Amplifier	AR	75A250	18464	Jul. 24, 2024	Jul. 23, 2025
CDN	ZHINAN	ZN3751	15004	Aug. 01, 2024	Jul. 31, 2026
6dB attenuator	ZHINAN	E-002	N/A	Jul. 24, 2024	Jul. 23, 2026
Power Probe	R&S	URV5-Z4	100124	Mar. 24, 2023	Mar. 23, 2025
Power Meter	R&S	NRVD	8323781027	Mar. 24, 2023	Mar. 23, 2025
Directional Coupler	Werlatone	C5571-10	99463	Feb. 01, 2024	Jan. 31, 2026
Signal Generator	Keysight	E4421B	MY43351603	Feb. 01, 2024	Jan. 31, 2025

Measuring Software

Software Name	Manufacturer	Details
TS+[JS35-CS]	Tonscend	For EMC measurement, version 2.0.1.7

11.4. Configuration of the EUT and method of measurement

- a. The Equipment Under Test (EUT) shall be tested within its intended operating and climatic conditions.
- b. The test generator and the coupling/decoupling network shall be placed directly on, and bonded to, the ground reference plane. The test shall be performed with the test generator connected to each of the coupling devices (CDN, EM clamp, current clamp) in turn. All other cables not under test shall either be disconnected (when functionally allowed) or provided with decoupling networks or unterminated CDNs only.
- c. The test shall be performed according to the above requirements and block diagram which shall specify the test setup.
- d. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Page 34 of 50

11.5. Test Summary

Test Engineer	Carpe Lin	Temperature	22.7 ℃
Test Date	2024-09-26	Air Pressure	985 Mbar
Test Mode(s)	Mode 1	Relative Humidity	51.3 %
Verdict	Pass		

Test port	Test Level	Coupling method	Observation	Performance
AC Mains Input	3 V	CDN	No degradation of performance	А



Page 35 of 50

12. Measurement of Fast Transients


12.1. Requirements

Port	⊠AC mains power ports	☐ signal, wired network and control ports ^a	☐ DC power ports ^a		
Basic Standard	IEC 61000-4-4				
Required Performance Criterion	В				
Test Level	1 kV (peak)	0.5 kV (peak)	0.5 kV (peak)		
Polarity	Positive/Negative				
Impulse Frequency	5kHz				
Impulse wave shape	5/50ns				
Burst Duration	15ms				
Burst Period	300ms				
Notes:					

Applicable only to ports which, according to the manufacturer's specification, supports cable lengths

12.2. Block Diagram of Test Setup

greater than 3 m.





Page 36 of 50

12.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
EFT/Surge Generator	Schaffner	Modula 6150	34437	May 24, 2024	May 23, 2025

Measuring Software

Software Name	Manufacturer	Details
WinModula	Schaffner	For EFT/Surge/Dips measurement, version 2.31 c

12.4. Configuration of the EUT and method of measurement

- a. The Equipment Under Test (EUT), whether stationary floor-mounted or table top, and equipment designed to be mounted in other configurations, shall be placed on a ground reference plane and shall be insulated from it by an insulating support 0,1 m ± 0,01 m thick.
- b. The test generator and the coupling/decoupling network shall be placed directly on, and bonded to, the ground reference plane.
- c. The EUT shall be arranged and connected to satisfy its functional requirements, according to the equipment installation specifications. The minimum distance between the EUT and all other conductive structures (e.g. the walls of a shielded room), except the ground reference plane shall be more than 0,5 m. All cables to the EUT shall be placed on the insulation support 0,1 m above the ground reference plane. Cables not subject to electrical fast transients shall be routed as far as possible from the cable under test to minimize the coupling between the cables.
- d. The test voltages shall be coupled to all of the EUT ports including those between two units of equipment involved in the test, unless the length of the interconnecting cable makes it impossible to test.
- e. Either a direct coupling network or a capacitive clamp shall be used for the application of the test voltages.
- f. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Report No.: AGC05443240944EE01

Page 37 of 50

12.5. Test Summary

Test Engineer	Carpe Lin	Temperature	22.7 ℃
Test Date	2024-09-26	Air Pressure	985 Mbar
Test Mode(s)	Mode 1	Relative Humidity	51.5 %
Verdict	Pass		

Inject Line	Voltage(kV)	Inject Method	Observation	Performance
AC Lines	0.5, 1	Direct	No degradation of performance	A



Report No.: AGC05443240944EE01

Page 38 of 50

13. Measurement of Surges

13.1. Requirements

Port	⊠ AC mains power ports ^a	☐ signal, wired network and control ports ^b	☐ DC network power ports ^b
Basic Standard	IEC 61000-4-5		
Required Performance Criterion	В В		В
Test Level	evel Line to line: 1 kV; Line to ground: 2 kV		Line to ground: 0.5 kV
Tr/Th	1.2/50 (8/20) µs		
Number of impulses	Five positive and five negative impulses		
Time between successive impulses	1 min		


Notes:

- a. The number of pulses applied shall be as follows:
 - Five positive pulses line-to-neutral at 90° phase.
 - Five negative pulses line-to-neutral at 270° phase.

The following additional pulses are required only if the EUT has an earth connection or if the EUT is earthed via any AE:

- Five positive pulses line-to-earth at 90° phase.
- Five negative pulses line-to-earth at 270° phase.
- Five negative pulses neutral-to-earth at 90° phase.
- Five positive pulses neutral-to-earth at 270° phase.
- b. Applicable only to ports which, according to the manufacturer's specification, supports cable lengths greater than 3 m.

13.2. Block Diagram of Test Setup





Report No.: AGC05443240944EE01

Page 39 of 50

13.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
EFT/Surge Generator	Schaffner	Modula 6150	34437	May 24, 2024	May 23, 2025

Measuring Software

Software Name	Manufacturer	Details	
WinModula	Schaffner	For EFT/Surge/Dips measurement, version 2.31 c	

13.4. Configuration of the EUT and method of measurement

- a. Verification shall be performed. It is preferable to perform the verification prior to the test.
- b. The test shall be performed according to the above requirements and block diagram which shall specify the test setup.
- c. When testing line-to-ground, the lines are tested individually in sequence, if there is no other specification.
- d. The test procedure shall also consider the non-linear current-voltage characteristics of the equipment under test. Therefore, all lower test levels including the selected test level shall be tested.
- e. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.

13.5. Test Summary

Test Engineer	Carpe Lin	Temperature	22.7 ℃
Test Date	2024-09-26	Air Pressure	985 Mbar
Test Mode(s)	Mode 1	Relative Humidity	51.5 %
Verdict	Pass		


Test port	Coupling	Voltage(kV)	Observation	Performance
AC Mains Input	line-to-neutral	0.5, 1	No degradation of performance	А




14. Photographs of Test Setup



Conducted emissions from the AC mains power ports



Radiated emissions at frequencies up to 1 GHz









Harmonic current emissions & Voltage fluctuations and flicker




Electrostatic discharge








Radio-frequency electromagnetic field up to 1 GHz



Radio-frequency common mode at the AC mains power ports








Fast transients/Surges at the AC mains power ports




15. Photographs of EUT




All view of EUT




Top view of EUT









Bottom view of EUT




Front view of EUT









Back view of EUT




Left view of EUT








Right view of EUT




Open view of EUT


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/









Battery view of EUT



Internal view-1 of EUT








Internal view-2 of EUT




Internal view-3 of EUT

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/







Internal view-4 of EUT

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.