

EMC Test Report

Report No.: AGC03485230603EE01

PRODUCT DESIGNATION: Round Bamboo wireless speaker

BRAND NAME : N/A

MODEL NAME : MO6428

APPLICANT: Mid Ocean Brands B.V.

DATE OF ISSUE : Jul. 04, 2023

STANDARD(S) : ETSI EN 301 489-1 V2.2.3 (2019-11) ETSI EN 301 489-17 V3.2.4 (2020-09)

REPORT VERSION: V1.0

Attestation of Global Configuration (Shenzhen) Co., Ltd



Page 2 of 48


REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jul. 04, 2023	Valid	Initial release




TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION	6
2. GENERAL INFORMATION	7
2.1. DESCRIPTION OF EUT	7
2.3. TEST STANDARDS AND RESULTS 2.4. TEST ITEMS AND THE RESULTS 2.5. ENVIRONMENTAL CONDITIONS	8
3. TEST MODE DESCRIPTION	9
4. MEASUREMENT UNCERTAINTY	10
5. SUPPORT EQUIPMENT	10
6. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION	11
7. RADIATED DISTURBANCE MEASUREMENT	13
7.1. LIMITS OF RADIATED DISTURBANCES	13 14
8. CONDUCTED EMISSION MEASUREMENT	19
8.1. LIMITS OF LINE CONDUCTED EMISSION	
9. HARMONIC CURRENT MEASUREMENT	23
9.1. LIMITS OF HARMONIC CURRENT	23 24
10. VOLTAGE FLUCTUATIONS AND FLICK MEASUREMENT	25
10.1. LIMITS OF VOLTAGE FLUCTUATIONS AND FLICK	






10.3. TEST SETUP	25
10.4. TEST RESULT	25
11. IMMUNITY TEST	26
11.1. DESCRIPTION OF PERFORMANCE CRITERIA	26
11.2. GENERAL PERFORMANCE CRITERIA	26
12. ELECTROSTATIC DISCHARGE IMMUNITY TEST	28
12.1 TEST SPECIFICATION	28
12.2 TEST PROCEDURE	28
12.3 TEST SETUP	29
12.4 TEST RESULT	31
12.5 PERFORMANCE	31
13. RADIATED, RADIO FREQUENCY ELECTROMAGNETIC FIELD IMMUNITY TEST	32
13.1. TEST SPECIFICATION	32
13.2. TEST PROCEDURE	32
13.3. TEST SETUP	33
13.4. TEST RESULT	34
13.5. PERFORMANCE	34
14. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST	35
14.1. TEST SPECIFICATION	35
14.2. TEST PROCEDURE	35
14.3. TEST SETUP	35
14.4. TEST RESULT	36
14.5. PERFORMANCE	36
15. SURGE IMMUNITY TEST	37
15.1. TEST SPECIFICATION	37
15.2. TEST PROCEDURE	37
15.3. TEST SETUP	37
15.4. TEST RESULT	38
15.5. PERFORMANCE	38
16. IMMUNITY TO CONDUCTED DISTURBANCES INDUCED BY RF FIELDS	39
16.1. TEST SPECIFICATION	39
16.2. TEST PROCEDURE Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedic	39





16.3. TEST SETUP	39
16.4. TEST RESULT	40
16.5. PERFORMANCE	40
17. VOLTAGE DIPS AND SHORT INTERRUPTIONS IMMUNITY TEST	41
17.1. TEST SPECIFICATION	41
17.2. TEST PROCEDURE	41
17.3. TEST SETUP	41
17.4. TEST RESULT	42
17.5. PERFORMANCE	42
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	43
APPENDIX B: PHOTOGRAPHS OF EUT	48





1. TEST REPORT CERTIFICATION

Applicant	Mid Ocean Brands B.V.		
Address	7/F., King Tower, 111King Lam Street, Cheung ShaWan, Kowloon, HongKong.		
Manufacturer	Mid Ocean Brands B.V.		
Address	7/F., King Tower, 111King Lam Street, Cheung ShaWan, Kowloon, HongKong.		
Factory	Mid Ocean Brands B.V.		
Address	7/F., King Tower, 111King Lam Street, Cheung ShaWan, Kowloon, HongKong.		
Product Designation	Round Bamboo wireless speaker		
Brand Name	N/A		
Test Model	MO6428		
Date of receipt of test item	Jun. 27, 2023		
Date of test	Jun. 27, 2023 to Jul. 04, 2023		
Deviation	None		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-EC-EMC		

We, Attestation of Global Compliance (Shenzhen) Co., Ltd., hereby certify that the submitted samples of the above item, as detailed in chapter 2.1 of this report, has been tested in our facility. The test record, data evaluation and test configuration represented herein are true and accurate accounts of measurements of the sample's EMC characteristics under the conditions herein specified.

Cici Li
(Project Engineer)

Reviewed By

Calvin Liu
(Reviewer)

Approved By

Max Zhang
(Authorized Officer)

Jul. 04, 2023

Jul. 04, 2023



Page 7 of 48

2. GENERAL INFORMATION

2.1. DESCRIPTION OF EUT

The EUT is a short range, lower power, Bluetooth device.

Details of technical specification refer to the description in follows:

Transmitter/Receiver (TX/RX)

ransmitter/Receiver (TX/RX)		
Operating Frequency	2402MHz to 2480MHz	
Bluetooth Version	V5.3	
INIOGUIATION Type	BR ⊠GFSK 1Mbps; EDR ⊠π /4-DQPSK 2Mbps ⊠8DPSK 3Mbps BLE ⊠GFSK 1Mbps ⊠GFSK 2Mbps	
Number of channels	79 Channels for BR/EDR;	
	40 Channels for BLE	
Hardware Version	V1.0	
Software Version	V1.0	
Antenna Type	PCB Antenna	
Antenna Gain	-0.58dBi	
Power Supply	DC 3.7V by battery or DC 5V by adapter	

2.2. OBJECTIVE

Perform Electro Magnetic Interference (EMI) and Electro Magnetic Susceptibility (EMS) tests for CE Marking.

2.3. TEST STANDARDS AND RESULTS

The EUT has been tested according to ETSI EN 301 489-1 V2.2.3 (2019-11) and ETSI EN 301 489-17 V3.2.4 (2020-09).

	ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part
ETSI EN 301 489-1	1: Common technical requirements; Harmonised Standard for ElectroMagnetic
	Compatibility.
	ElectroMagnetic Compatibility (EMC) standard for radio equipment and services;
ETSI EN 301 489-17	Part 17: Specific conditions for Broadband Data Transmission Systems;
	Harmonised Standard for ElectroMagnetic Compatibility



Page 8 of 48

2.4. TEST ITEMS AND THE RESULTS

No.	Basic Standard	Test Type	Result
EMIS	EMISSION (EN 301 489-1 §7.1)		
1	EN 55032	Radiated emission	PASS
2	EN 55032	Conducted emission, AC ports	PASS
3	EN 55032	Conducted emission, Telecom ports	N/A
4	EN 61000-3-2	Harmonic current emissions	N/A
5	EN 61000-3-3	Voltage fluctuations & flicker	PASS
IMM	IMMUNITY (EN 301 489-1 §7.2)		
6	EN 61000-4-2	Electrostatic discharge immunity	PASS
7	EN 61000-4-3	Radiated RF electromagnetic field immunity	PASS
8	EN 61000-4-4	Electrical fast transient/burst immunity	PASS
9	ISO 7637-1, -2	Transients and surges, DC ports	N/A
10	EN 61000-4-5	Surge immunity, AC ports, Telecom ports	PASS
11	EN 61000-4-6	Immunity to conducted disturbances induced by RF fields	PASS
12	EN 61000-4-11	Voltage dips and short interruptions immunity	PASS

Note: 1. N/A- Not Applicable.

2. The latest versions of basic standards are applied.

2.5. ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35°CRelative humidity: 30-60%

- Atmospheric pressure: 86-106kPa



Page 9 of 48

3. TEST MODE DESCRIPTION

TEST MODE DESCRIPTION				
NO.	EMI TEST MODE DESCRIPTION	WORST		
1	BT mode with charging	V		
2	BT mode	-		
NO.	EMS TEST MODE DESCRIPTION	WORST		
1	BT mode with charging	V		
2	BT mode	-		
Note: 1. V means EMI worst mode.				
2. All modes have been tested and only the worst mode test data recorded in the test report.				

I/O Port Information (⊠Applicable □Not Applicable)

I/O Port of EUT			
I/O Port Type	Number	Cable Description	Tested With
Type-C Port	1	0.45m unshielded	1



Page 10 of 48

4. MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in measurement" (GUM) published by CISPR and ANSI.

- Uncertainty of Conducted Emission, Uc = ±2.9 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.9 dB

5. SUPPORT EQUIPMENT

Device Type	Manufacturer	Model Name	Data Cable
iPod	APPLE	MGG82ZP/A	
Adapter	jinbaotong	K-T10E0502000E	

Note: 1."-- "means no any support device during testing.

2. All the cables were provided by AGC Lab.



Page 11 of 48

6. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Aug. 04, 2022	Aug. 03, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024
Test Software	FARA	EZ-EMC(Ver. AGC-CON03A1)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Mar. 23, 2023	Mar. 22, 2024
Preamplifier Assembly	ETS	3117PA	00225134	Sep. 02, 2022	Sep. 01, 2024
Wideband Antenna	SCHWARZBEC K	VULB9168	VULB9168-49 4	Jan. 05, 2023	Jan. 04, 2025
Test Software	FARA	EZ-EMC(Ver.RA- 03A)	N/A	N/A	N/A
Test Software	Tonscend	JS32-RE(Ver.2.5)	N/A	N/A	N/A

TEST EQUIPMENT OF POWER HARMONICS / VOLTAGE FLUCTUATION / FLICKER TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Conditioning Unit	Schaffner	CCN1000-1	72431	Jul. 06, 2022	Jul. 05, 2023
AC Source	Schaffner	NSG1007	56825	Jun. 02, 2023	Jun. 01, 2024
Test software	TC	4.29.0	N/A	N/A	N/A

TEST EQUIPMENT OF ESD TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
ESD Simulator	Schaffner	NSG 438	782	Dec. 30, 2022	Dec. 29, 2023



Page 12 of 48

TEST EQUIPMENT OF SURGE/EFT/DIPS TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
EFT/Surge Generator	Schaffner	Modula 6150	34437	Jun. 08, 2023	Jun. 07, 2024
Test software	TC	2.31	N/A	N/A	N/A

TEST EQUIPMENT OF RS IMMUNITY TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Generator	Aglient	E4421B	MY43351603	Feb. 17, 2023	Feb. 16, 2024
Power Probe	R&S	URV5-Z4	100124	Mar. 24, 2023	Mar. 23, 2025
Power Meter	R&S	NRVD	8323781027	Mar. 24, 2023	Mar. 23, 2025
Power Amplifier	L2	S2006-0001	BPA00T10W 500-1	N/A	N/A
Power Amplifier	Milmega	AS0104-55_55	5_55 1004793		N/A
Power Amplifier	Rflight	NTWPA-25601 00	17063183	N/A	N/A
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00034609	Mar. 23, 2023	Mar. 22, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-4 94	Jan. 05, 2023	Jan. 04, 2025
Bi-log antenna	ETS	3142C	920250	Jun. 08, 2022	Jun. 07, 2024
Test Software	Tonscend	2.0.1.8	N/A	N/A	N/A

TEST EQUIPMENT OF CS IMMUNITY TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power Amplifier	AR	75A250	18464	N/A	N/A
CDN	ZHINAN	ZN3751	15004	Aug. 03, 2022	Sep. 02, 2024
6dB attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Power Probe	R&S	URV5-Z4	100124 Mar. 24, 2023		Mar. 23, 2025
Electromagnetic Injection Clamp	Luthi	EM101	35773	Aug. 12, 2022	Aug. 11, 2024
Power Meter	R&S	NRVD	RVD 8323781027 Mar. 24, 20		Mar. 23, 2025
Signal Generator	Aglient	E4421B	MY43351603	Feb. 17, 2023	Feb. 16, 2024
Test Software	Tonscend	2.0.1.7	N/A	N/A	N/A



Page 13 of 48

7. RADIATED DISTURBANCE MEASUREMENT

7.1. LIMITS OF RADIATED DISTURBANCES

Limits for radiated disturbance 30M to1 GHz at a measurement distance of 3m

Frequency range (MHz)	Quasi peak limits(dBuV/m), for Class B ITE, at 3m measurement distance
30-230	40
230-1000	47

Limits for radiated disturbance above 1 GHz at a measurement distance of 3m

Fraguency range (MU=)	Limits (dBu\	//m), Class B ITE
Frequency range (MHz)	Peak	Average
1000-3000	70	50
3000-6000	74	54

Note: 1. The lower limit shall apply at the transition frequency.

2. Additional provisions may be required for cases where interference occurs.


7.2. TEST PROCEDURE

- (1). The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2). The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- (3). The antenna is a broadband antenna, and its height is varied from 1 to 4 meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- (4). For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to the heights from 1 to 4 meters and the ratable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- (5). The test-receiver system was set to Peak Detector Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emission that did not have 10dB margin would be retested one by one using the quasi-peak method.




7.3. BLOCK DIAGRAM OF TEST SETUP

Radiated Disturbance below 1 GHz



Radiated Disturbance above 1 GHz



For the actual test configuration, please refer to the related item-Photographs of the Test Configuration.




7.4. TEST RESULT

The test modes were carried out for all modes.

The worst test mode of the EUT was Mode 1, and its test data was showed as the follow:

RADIATED EMISSION BELOW 1GHz-HORIZONTAL



No.	MI	c. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	136.4598	19.65	15.41	35.06	40.00	-4.94	peak
2		185.1379	19.09	12.79	31.88	40.00	-8.12	peak
3		290.0172	25.89	14.70	40.59	47.00	-6.41	peak
4		327.8873	21.39	16.13	37.52	47.00	-9.48	peak
5		620.7096	6.31	25.13	31.44	47.00	-15.56	peak
6		896.9965	6.41	31.42	37.83	47.00	-9.17	peak

RESULT: PASS



RADIATED EMISSION BELOW 1GHz- VERTICAL




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	32.5198	22.83	14.43	37.26	40.00	-2.74	QP
2	İ	44.1202	18.45	16.94	35.39	40.00	-4.61	peak
3	İ	60.0691	18.10	17.10	35.20	40.00	-4.80	peak
4	İ	118.1862	17.84	17.38	35.22	40.00	-4.78	peak
5	İ	142.8243	16.50	18.20	34.70	40.00	-5.30	QP
6	İ	266.6089	23.43	18.06	41.49	47.00	-5.51	peak

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz - HORIZONTAL




NO	Freq.	Level	Factor	Limit	Margin	Height	Angle	Delevite
NO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Polarity
1	1210.2102	30.73	-19.88	70.00	39.27	100	160	Horizontal
2	1710.7107	33.25	-18.28	70.00	36.75	100	310	Horizontal
3	2381.3814	37.91	-13.81	70.00	32.09	100	250	Horizontal
4	3142.1421	41.38	-10.80	74.00	32.62	100	220	Horizontal
5	4203.2032	43.18	-7.86	74.00	30.82	100	190	Horizontal
6	5774.7748	43.72	-5.65	74.00	30.28	100	280	Horizontal

RESULT: PASS



RADIATED EMISSION ABOVE 1GHz - VERTICAL



NO	Freq.	Level	Factor	Limit	Margin	Height	Angle	Delevite	
NO.	[MHz]	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	Polarity	
1	1185.1852	31.36	-19.87	70.00	38.64	100	170	Vertical	
2	1745.7457	33.73	-18.01	70.00	36.27	100	120	Vertical	
3	2521.5215	37.85	-13.04	70.00	32.15	100	300	Vertical	
4	3592.5926	42.73	-9.40	74.00	31.27	100	250	Vertical	
5	4803.8038	44.70	-6.78	74.00	29.30	100	330	Vertical	
6	5854.8549	44.48	-5.38	74.00	29.52	100	300	Vertical	

RESULT: PASS



Page 19 of 48

8. CONDUCTED EMISSION MEASUREMENT

8.1. LIMITS OF LINE CONDUCTED EMISSION

Fraguency range (MUT)	Limits (dBuV) Class B ITE			
Frequency range (MHz)	Quasi-peak	Average		
0.15-0.50	66 to 56	56 to 46		
0.50-5	56	46		
5-30	60	50		

Note: 1. The lower limit shall apply at the transition frequencies.


2. The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

8.2. TEST PROCEDURE

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per EN 55032 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per EN 55032.
- (3) All I/O cables were positioned to simulate typical actual usage as per EN 55032.
- (4) The EUT received DC 5V power from adapter which received AC 230V 50Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- (5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the AN powering the EUT. The AN has two monitoring points: Line 1 (Positive) and Line 2 (Negative). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (6) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- (7) During the above scans, the emissions were maximized by cable manipulation.
- (8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- (9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.



8.3. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.




8.4. TEST RESULT

The test modes were carried out for all modes.

The worst test mode of the EUT was Mode 1, and its test data was showed as the follow:

LINE CONCUTED EMISSION TEST-L



MEASUREMENT RESULT: "agc fin"

2023/6/28 21:29

2023/6/20 21:	23					
Frequency MHz	Level dBµV		Limit dBµV	Margin dB	Detector	Line
0.550000	47.90	6.1	56	8.1	QP	L1
1.646000	49.10	6.2	56	6.9	QP	L1
2.722000	45.70	6.3	56	10.3	QP	L1
2.742000	48.90	6.3	56	7.1	QP	ь1
3.822000	46.30	6.3	56		QP	L1
4.934000	47.90	6.3	56	8.1	OP	T ₁ 1

MEASUREMENT RESULT: "agc fin2"


2023/6/28 21:28

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.530000	36.80	6.1	46	9.2	AV	L1
0.546000	43.70	6.1	46	2.3	AV	L1
1.646000	41.50	6.2	46	4.5	AV	L1
2.742000	39.50	6.3	46	6.5	AV	L1
3.826000	29.70	6.3	46	16.3	AV	L1
3.842000	33.80	6.3	46	12.2	AV	L1

RESULT: PASS



LINE CONCUTED EMISSION TEST-N



MEASUREMENT RESULT: "agc_fin"

2023/6/28 21:35

2023/0/20 21.	. 55					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.522000	45.30	6.1	56	10.7	QP	N
1.050000	40.30	6.2	56	15.7	QP	N
1.346000	40.60	6.2	56	15.4	QP	N
1.618000	43.40	6.2	56	12.6	QP	N
2.714000	44.50	6.3	56	11.5	QP	N
4.870000	46.10	6.3	56	9.9	QP	N

MEASUREMENT RESULT: "agc fin2"

2023/6/28 21:35

, .,	-					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.502000	30.60	6.1	46	15.4	AV	N
0.522000	37.20	6.1	46	8.8	AV	N
1.618000	35.20	6.2	46	10.8	AV	N
2.714000	29.80	6.3	46	16.2	AV	N
3.806000	30.40	6.3	46	15.6	AV	N
4.910000	33.10	6.3	46	12.9	AV	N

RESULT: PASS



Page 23 of 48

9. HARMONIC CURRENT MEASUREMENT

9.1. LIMITS OF HARMONIC CURRENT

Limits for	Limits for Class A Equipment				
Harmonics Order n	Max. permissible harmonic current (A)				
Od	d harmonics				
3	2.30				
5	1.14				
7	0.77				
9	0.40				
11	0.33				
13	0.21				
15≤n≤39	0.15×15/n				
Eve	en harmonics				
2	1.08				
4	0.43				
6	0.30				
8≤n≤40	0.23×8/n				

Note: 1. According to section 5 of EN 61000-3-2: 2014, the EUT is Class A equipment.


2. The above limits are for all applications having an active input power>75W. No limits apply for equipment with an active input power up to and including 75W.

9.2. TEST PROCEDURE

- 1. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- 2. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the necessary for the EUT to be exercised.



9.3. TEST SETUP



For the actual test configuration, please refer to Appendix A: Photographs of the Test Configuration.

9.4. TEST RESULT

Note: Owning to the power of EUT is less than 75W, so test is not applicable.



Page 25 of 48

10. VOLTAGE FLUCTUATIONS AND FLICK MEASUREMENT

10.1. LIMITS OF VOLTAGE FLUCTUATIONS AND FLICK

Test Item	Test Item Limit Note		
P _{st}	1.0	P _{st} means Short-term flicker indicator	
P _{lt}	0.65	P _{lt} means long-term flicker indicator	
T _{dt}	0.5	T_{dt} means maximum time that d_{t} exceeds 3%	
d _{max} (%)	4%	d _{max} means maximum relative voltage change.	
d _c (%)	3.3%	d _c means relative steady-state voltage change.	

10.2. TEST PROCEDURE

- 1. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal conditions
- 2. During the flick measurement, the measure time shall include that part of whole operation changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

10.3. TEST SETUP

Same as 9.3

10.4. TEST RESULT

Test Specification

Test Frequency	50Hz	Test Voltage	230V AC
Waveform	Sine Test Time		10 minutes(P _{st}); 2 hours (P _{lt})

Test Result

Test Parameter	Measurement Value	Limit	Remarks
P _{st}	0.261	1.0	Pass
P _{lt}	0.114	0.65	Pass
$T_{dt(s)}$	0.0	0.5	Pass
d _{max} (%)	0.00	4%	Pass
d _c (%)	0.00	3.3%	Pass



Page 26 of 48

11. IMMUNITY TEST

11.1. DESCRIPTION OF PERFORMANCE CRITERIA

The performance criteria are used to take a decision on whether a radio equipment passes or fails immunity tests.

For the purpose of the present document two categories of performance criteria apply:

- · Performance criteria for continuous phenomena.
- Performance criteria for transient phenomena.

11.2. GENERAL PERFORMANCE CRITERIA

1. Performance criteria for continuous phenomena

During the test, the equipment shall:

- · continue to operate as intended;
- · not unintentionally transmit;
- not unintentionally change its operating state;
- not unintentionally change critical stored data.

2. Performance criteria for transient phenomena

For all ports and transient phenomena with the exception described below, the following applies:

- The application of the transient phenomena shall not result in a change of the mode of operation (e.g. unintended transmission) or the loss of critical stored data.
- After application of the transient phenomena, the equipment shall operate as intended.

For surges applied to symmetrically operated wired network ports intended to be connected directly to outdoor lines the following criteria applies:

- For products with only one symmetrical port intended for connection to outdoor lines, loss of function is allowed, provided the function is self-recoverable, or can be otherwise restored. Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.
- For products with more than one symmetrical port intended for connection to outdoor lines, loss of function on the port under test is allowed, provided the function is self-recoverable. Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

For a 0 % residual voltage dip tests the following performance criteria apply:

• The performance criteria for transient phenomena shall apply.

For a 70 % residual voltage dip and voltage interruption tests, the following performance criteria apply:

- in the case where the equipment is fitted with or connected to a battery back-up, the performance criteria for transient phenomena shall apply;
- in the case where the equipment is powered solely from the AC mains supply (without the use of a parallel battery back-up) volatile user data may have been lost and if applicable the communication link need not to be maintained and lost functions should be recoverable by user or operator;
- no unintentional responses shall occur at the end of the test, when the voltage is restored to nominal;
- in the event of loss of function(s) or in the event of loss of user stored data, this fact shall be recorded.



Page 27 of 48

3. Performance Table

	EN 301 489-17 Performance criteria						
Criteria	During Test	After Test (i.e. as a result of the application of the test)					
А	Shall operate as intended. (see note). Shall be no loss of function. Shall be no unintentional transmissions.	Shall operate as intended. Shall be no degradation of performance. Shall be no loss of function. Shall be no loss of critical stored data.					
В	May be loss of function.	Functions shall be self-recoverable. Shall operate as intended after recovering. Shall be no loss of critical stored data.					
С	May be loss of function.	Functions shall be recoverable by the operator. Shall operate as intended after recovering. Shall be no loss of critical stored data.					

The performance criteria A shall apply for continuous phenomena.

The performance criteria B shall apply for transient phenomena, except for voltage dips greater than or equal to 100 ms and voltage interruptions of 5 000 ms duration, for which performance criteria C shall apply.

Where the EUT is a transmitter in standby mode or receive mode, unintentional transmission shall not occur during the test.

Note: Operate as intended during the test allows a level of degradation in accordance with the Minimum performance level.

Minimum performance level

For equipment that supports a PER or FER, the minimum performance level shall be a PER or FER less than or equal to 10 %.

For equipment that does not support a PER or a FER, the minimum performance level shall be no loss of the wireless transmission function needed for the intended use of the equipment.



Page 28 of 48

12. ELECTROSTATIC DISCHARGE IMMUNITY TEST

12.1 TEST SPECIFICATION

Basic Standard	EN 61000-4-2		
Discharge Impedance 330Ω / 150 pF			
Discharge Voltage Air Discharge ±8kV, Contact Discharge ±4kV			
Polarity Positive / Negative			
Number of Discharge Minimum 25 times at each test point			
Discharge Mode	Single discharge		
Discharge Period	1-second minimum		


12.2 TEST PROCEDURE

The test procedure was in accordance with EN 61000-4-2:

- a. Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- b. The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- c. The time interval between two successive single discharges was at least 1 second.
- d. The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the EUT.
- e. Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- f. Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were completed.
- g. At least ten single discharges (in the most sensitive polarity) were applied to the Horizontal Coupling Plane at points on each side of the EUT. The ESD generator was positioned vertically at a distance of 0.1 meters from the EUT with the discharge electrode touching the HCP.
- h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane in sufficiently different positions that the four faces of the EUT were completely illuminated. The VCP (dimensions 0.5m×0.5m) was placed vertically to and 0.1 meters from the EUT.



12.3 TEST SETUP



For the actual test configuration, please refer to Appendix A: Photographs of the Test Configuration.



Page 30 of 48

ESD LOCATION:

Blue line: Air discharge Red line: Contact discharge





Page 31 of 48

12.4 TEST RESULT

Times of Discharge	Voltage	Coupling	Test Mode	Performance criteria
Mini 25 / Point	±2kV; ±4kV	Contact discharge	Mode 1/2	А
Mini 25 / Point	±2kV; ±4kV; ±8kV	Air Discharge	Mode 1/2	А
Mini 25 / Point	±4kV	Indirect Discharge HCP	Mode 1/2	А
Mini 25 / Point	±4kV	Indirect Discharge VCP	Mode 1/2	А
A: No degradation in the performance of the EUT was observed.				

Note: operating mode include all modes of EMS in page 9.

12.5 PERFORMANCE

⊠Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
☐Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
☐Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.
⊠ Compliance	e

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection
Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results
presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report.
Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Page 32 of 48

13. RADIATED, RADIO FREQUENCY ELECTROMAGNETIC FIELD IMMUNITY TEST 13.1. TEST SPECIFICATION

10.11. TEOT OF EOII TOATIG			
Basic Standard	EN 61000-4-3		
Frequency Range	80 MHz – 6000MHzMHz		
Field Strength	3V/m		
Modulation	1 kHz sine wave, 80%, AM modulation		
Frequency Step	1% of fundamental		
Polarity of Antenna	Horizontal and Vertical		
Test Distance	3m		
Antenna Height	1.55m		
Dwell Time	3 seconds		


13.2. TEST PROCEDURE

The test procedure was in accordance with EN 61000-4-3.

- a. The testing was performed in a fully anechoic chamber. The transmit antenna was located at a distance of 3 meters from the EUT.
- b. The test signal was 80% amplitude modulated with a 1 kHz sine wave.
- c. The frequency range was swept from 80 MHz to 6000MHz with the exception of the exclusion band for transmitters, receivers and duplex transceivers. The rate of sweep did not exceed 1.5×10⁻³ decade/s. Where the frequency range is swept incrementally, the step size was 1% of fundamental.
- d. The dwell time at each frequency shall be not less than the time necessary for the EUT to be able to respond.
- e. The field strength level was 3V/m.
- f. The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.



13.3. TEST SETUP



For the actual test configuration, please refer to Appendix A: Photographs of the Test Configuration.



Page 34 of 48

13.4. TEST RESULT

Freq. Range (MHz)	Field	Modulation	Polarity	Position	Test Mode	Performance criteria
80-6000	3V/m	Yes	Н	Front	Mode 1/2	Α
80-6000	3V/m	Yes	Н	Back	Mode 1/2	А
80-6000	3V/m	Yes	Н	Left	Mode 1/2	А
80-6000	3V/m	Yes	Н	Right	Mode 1/2	А
80-6000	3V/m	Yes	V	Front	Mode 1/2	А
80-6000	3V/m	Yes	V	Back	Mode 1/2	А
80-6000	3V/m	Yes	V	Left	Mode 1/2	А
80-6000	3V/m	Yes	V	Right	Mode 1/2	А

A: No degradation or PER < 10% in the performance of the EUT was observed.

Note: operating mode include all modes of EMS in page 9.

13.5. PERFORMANCE

⊠Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
☐Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
☐Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.
	☐ Not Compliance



14. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST


14.1. TEST SPECIFICATION

Basic Standard	EN 61000-4-4	
Test Voltage	a.c. power port – 1 kV	
Polarity	Positive/Negative	
Impulse Frequency	5kHz	
Impulse wave shape	5/50ns	
Burst Duration	15ms	
Burst Period	300ms	
Test Duration	Not less than 1 min.	

14.2. TEST PROCEDURE

- 1. The EUT was tested with 1000 volt discharges to the AC power input leads.
- 2. Both positive and negative polarity discharges were applied.
- 3. The length of the "hot wire" from the coaxial output of the EFT generator to the terminals on the EUT should not exceed 1 meter.
- 4. The duration time of each test sequential was 1 minute.
- 5. The transient/burst waveform was in accordance with IEC 61000-4-4, 5/50ns.

14.3. TEST SETUP



For the actual test configuration, please refer to Appendix A: Photographs of the Test Configuration.



Page 36 of 48

14.4. TEST RESULT

Test Point	Polarity	Test Level (kV)	Test Mode	Performance criteria
a.c. port, L	+/-	1	Mode 1	А
a.c. port, N	+/-	1	Mode 1	А
a.c. port, L-N	+/-	1	Mode 1	А
a.c. port, L-N	+/-	1	Mode 1	А

A: No degradation in the performance of the EUT was observed.

Note: operating mode include all modes of EMS in page 9.

14.5. PERFORMANCE

14.5. PERFURI	WANCE
⊠Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
☐Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
☐Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.
	Not Compliance

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection
Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results
presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report.
Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



15. SURGE IMMUNITY TEST


15.1. TEST SPECIFICATION

Basic Standard	EN 61000-4-5
Waveform	Voltage 1.2/50 μs; Current 8/20 μs
Test Voltage	a.c. power port, line to line 1.0 kV
Polarity	Positive/Negative
Phase Angle	0°, 90°, 180°, 270°
Repetition Rate	60sec
Times	5 time/each condition.

15.2. TEST PROCEDURE

- a. The EUT and the auxiliary equipment were placed on a table of 0.8m heights above a metal ground reference plane. The size of ground plane is greater than 1m×1m and project beyond the EUT by at least 0.1m on all sides. The ground plane is connected to the protective earth. The length of power cord between the coupling device and the EUT was less than 2 meters (provided by the manufacturer).
- b. The EUT was connected to the power mains through a coupling device that directly couples the surge interference signal. The surge noise was applied synchronized to the voltage phase at the zero crossing and the peak value of the AC voltage wave (positive and negative).
- c. The surges were applied line to line and line(s) to earth. All lower levels including the selected test level were tested. The polarity of each surge level included positive and negative test pulses.

15.3. TEST SETUP



For the actual test configuration, please refer to Appendix A: Photographs of the Test Configuration.



Page 38 of 48

15.4. TEST RESULT

Coupling Line	Polarity	Voltage (kV)	Test Mode	Performance criteria	
a.c. power, L-N	+/-	1.0	Mode 1	А	
A: No degradation in the performance of the EUT was observed.					

Note: operating mode include all modes of EMS in page 9.

15.5. PERFORM	MANCE
⊠Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
□Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
☐Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.
⊠ Complianc	e 🗌 Not Compliance

	☐ Not Compliance
--	------------------



16. IMMUNITY TO CONDUCTED DISTURBANCES INDUCED BY RF FIELDS


16.1. TEST SPECIFICATION

Basic Standard	EN 61000-4-6
Frequency Range	0.15 MHz – 80 MHz
Field Strength	3Vrms
Modulation	1 kHz Sine Wave, 80% AM
Frequency Step	1% of fundamental
Coupled Cable	a.c. power line
Coupling Device	CDN-M2

16.2. TEST PROCEDURE

- 1. The EUT shall be tested within its intended operating and climatic conditions.
- 2. The test shall be performed with the test generator connected to each of the coupling and decoupling devices in turn, while the other non-excited RF input ports of the coupling devices are terminated by a 50-ohm load resistor.
- 3. The test signal was 80% amplitude modulated with a 1 kHz sine wave
- 4. The frequency range is swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80% amplitude. The sweep rate shall not exceed 1.5×10-3 decades/s. The step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value where the frequency is swept incrementally.
- The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised, and able to respond. Sensitive frequencies such as clock frequencies and harmonics or frequencies of dominant interest, shall be analyzed separately.
- 6. Attempts should be made to fully exercise the EUT during test, and to fully interrogate all exercise modes selected for susceptibility.

16.3. TEST SETUP



For the actual test configuration, please refer to Appendix A: Photographs of the Test Configuration.



Page 40 of 48

16.4. TEST RESULT

Test Point	Frequency (MHz)	Level (V rms)	Test Mode	Performance criteria	
a.c. port	0.15 – 80	3	Mode 1	А	
A: No degradation in the performance of the EUT was observed.					

Note: operating mode include all modes of EMS in page 9.

16.5. PERFORI	MANCE
⊠Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
☐Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
☐Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.
	e



17. VOLTAGE DIPS AND SHORT INTERRUPTIONS IMMUNITY TEST


17.1. TEST SPECIFICATION

Basic Standard	EN 61000-4-11	
	100% reduction, 0.5 Cycle	
Voltage Dips	100% reduction, 1.0 Cycle	
	30% reduction, 25 Cycles	
Voltage Interruptions	100% reduction, 250 Cycles	
Voltage Phase Angle	0°, 45°, 90°, 135°, 180°, 225°, 270°, 315°	

17.2. TEST PROCEDURE

- a). The power cord was used as supplied by the manufacturer. The EUT was connected to the line output of the Voltage Dips and Interruption Generator.
- b). The EUT was tested for (1) 100% voltage dip of supplied voltage with duration of 0.5 cycles, (2)100% voltage dip of supplied voltage and duration 1.0 cycle. (3) 30% voltage dip of supplied voltage and duration 25 cycles. (4) 100% voltage interruption of supplied voltage with duration of 250 Cycles was followed.
- c). Voltage reductions occur at 0 degree crossover point of the voltage waveform. The performance of the EUT was checked after the voltage dip or interruption.

17.3. TEST SETUP



For the actual test configuration, please refer to Appendix A, Photographs of the Test Configuration.



Page 42 of 48

17.4. TEST RESULT

Test Mode	Voltage Reduction	Duration (cycle)	Times	Interval (Sec)	Test Mode	Performance criteria
	100%	0.5	3	10	Mode 1	В
Voltage dips	100%	1	3	10	Mode 1	В
	30%	25	3	10	Mode 1	С
Voltage interruptions	100%	250	3	10	Mode 1	С

A: No degradation in the performance of the EUT was observed.

B: Stop charging during the test and self-recoverable after test.


C: Lost functions can be recoverable by user or operator.

Note: operating mode include all modes of EMS in page 9.

17.5. PERFORMANCE

17.3.1 LINI ONNIA	NOL
□Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
⊠Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
⊠Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

⊠ Compliance	☐ Not Compliance	
--------------	------------------	--






APPENDIX A: PHOTOGRAPHS OF TEST SETUP

LINE CONDUCTED EMISSION TEST SETUP




RADIATED EMISSION TEST SETUP BELOW 1GHZ





RADIATED EMISSION TEST SETUP ABOVE 1GHZ



EN 61000-3-3 VOLTAGE FLUCTUATION / FLICKER TEST SETUP







EN 61000-4-2 ESD TEST SETUP




EN 61000-4-3 RS TEST SETUP BELOW 1GHZ








EN 61000-4-3 RS TEST SETUP ABOVE 1GHZ




EN 61000-4-4/-5/-11 EFT/SURGE/DIPS IMMUNITY TEST SETUP







EN 61000-4-6 CS IMMUNITY TEST SETUP





Page 48 of 48

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC03485230603AP01

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.