



中国认可
国际互认
检测
TESTING
CNAS L4062



TEST REPORT

Reference No..... : WTF23X12257064W003
Manufacturer..... : Mid Ocean Brands B.V.
Address..... : 7/F., Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Factory..... : 115164
Product Name..... : LED Wireless speaker
Model No..... : MO6662
Standards..... : EN 55032:2015+A1:2020; EN 55035:2017+A11:2020
EN IEC 61000-3-2:2019+A1:2021; EN 61000-3-3:2013+A2:2021
ETSI EN 301 489-1 V2.2.3 (2019-11)
Draft ETSI EN 301 489-17 V3.2.5 (2022-08)
Date of Receipt sample : 2023-12-01
Date of Test..... : 2023-12-01 to 2023-12-26
Date of Issue..... : 2023-12-26
Test Report Form No. : WTX_ETSI EN 301 489_1_2019W
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Gala Wang

Approved by:

Silin Chen



TABLE OF CONTENTS

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
1.2 TEST STANDARDS.....	6
1.3 TEST METHODOLOGY.....	6
1.4 TEST FACILITY.....	7
1.5 EUT SETUP AND OPERATION MODE.....	8
1.6 PERFORMANCE CRITERIA FOR EMS.....	9
1.7 MEASUREMENT UNCERTAINTY.....	11
1.8 TEST EQUIPMENT LIST AND DETAILS.....	12
2. SUMMARY OF TEST RESULTS.....	15
3. CONDUCTED EMISSIONS.....	16
3.1 TEST PROCEDURE.....	16
3.2 BASIC TEST SETUP BLOCK DIAGRAM.....	16
3.3 ENVIRONMENTAL CONDITIONS.....	16
3.4 CONDUCTED EMISSIONS TEST DATA.....	16
4. RADIATED EMISSIONS.....	25
4.1 TEST PROCEDURE.....	25
4.2 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	25
4.3 ENVIRONMENTAL CONDITIONS.....	26
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	26
5. HARMONIC CURRENT EMISSIONS.....	42
5.1 TEST SETUP BLOCK DIAGRAM.....	42
5.2 TEST STANDARDS.....	42
5.3 ENVIRONMENTAL CONDITIONS.....	42
5.4 HARMONIC CURRENT EMISSIONS TEST DATA.....	42
6. VOLTAGE FLUCTUATION AND FLICKER.....	48
6.1 TEST SETUP BLOCK DIAGRAM.....	48
6.2 TEST STANDARDS.....	48
6.3 ENVIRONMENTAL CONDITIONS.....	48
6.4 VOLTAGE FLUCTUATION AND FLICKER TEST DATA.....	48
7. ELECTROSTATIC DISCHARGE (ESD).....	50
7.1 TEST SETUP BLOCK DIAGRAM.....	50
7.2 TEST PERFORMANCE.....	50
7.3 ENVIRONMENTAL CONDITIONS.....	50
7.4 ELECTROSTATIC DISCHARGE IMMUNITY TEST DATA.....	50
8. RADIO FREQUENCY ELECTROMAGNETIC FIELD (R/S).....	52
8.1 TEST SETUP BLOCK DIAGRAM.....	52
8.2 TEST PERFORMANCE.....	52
8.3 ENVIRONMENTAL CONDITIONS.....	52
8.4 CONTINUOUS RADIATED DISTURBANCES TEST DATA.....	52
9. FAST TRANSIENTS, COMMON MODE (EFT).....	54
9.1 TEST SETUP BLOCK DIAGRAM.....	54
9.2 TEST PERFORMANCE.....	54
9.3 ENVIRONMENTAL CONDITIONS.....	54
9.4 ELECTRICAL FAST TRANSIENTS TEST DATA.....	54
10. SURGES.....	56
10.1 TEST SETUP BLOCK DIAGRAM.....	56
10.2 TEST PERFORMANCE.....	56
10.3 ENVIRONMENTAL CONDITIONS.....	56
10.4 SURGE TEST DATA.....	56



11. RADIO FREQUENCY, COMMON MODE (C/S)	58
11.1 TEST SETUP BLOCK DIAGRAM	58
11.2 TEST PERFORMANCE	58
11.3 ENVIRONMENTAL CONDITIONS	58
11.4 CONTINUOUS CONDUCTED DISTURBANCES TEST DATA	58
12. VOLTAGE DIPS AND INTERRUPTIONS	60
12.1 TEST SETUP BLOCK DIAGRAM	60
12.2 TEST PERFORMANCE	60
12.3 ENVIRONMENTAL CONDITIONS	60
12.4 VOLTAGE DIPS AND INTERRUPTIONS TEST DATA	60
EXHIBIT 1 - EUT PHOTOGRAPHS	61
EXHIBIT 2 - TEST SETUP PHOTOGRAPHS	62

WALTEK



Report version

Version No.	Date of issue	Description
Rev.00	2023-12-26	Original
/	/	/

WALTEK



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	LED Wireless speaker
Trade Name:	/
Model No.:	MO6662
Adding Model(s):	/
Rated Voltage:	DC3.7V
Battery Capacity:	1800mAh
Power Adapter:	/
Software Version:	/
Hardware Version:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth	
Bluetooth Version:	Bluetooth V5.0(EDR Mode)
Frequency Range:	2402MHz-2480MHz
Max.RF Output Power:	2.84dBm (EIRP)
Type of Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Data Rate:	1Mbps, 2Mbps, 3Mbps
Quantity of Channels	79
Channel Separation:	1MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	1.2dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	



1.2 Test Standards

The tests were performed according to following standards:

EN 55032:2015+A1:2020: Electromagnetic compatibility of multimedia equipment - Emission requirements

EN 55035:2017+A11:2020: Electromagnetic compatibility of multimedia equipment - Immunity requirements.

EN IEC 61000-3-2:2019+A1:2021: Electromagnetic compatibility (EMC) -- Part 3-2: Limits - Limits for harmonic current emissions (equipment input current up to and including 16 A per phase).

EN 61000-3-3:2013+A2:2021: Electromagnetic compatibility (EMC) -- Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection.

ETSI EN 301 489-1 V2.2.3 (2019-11): Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard for Electromagnetic Compatibility.

Draft ETSI EN 301 489-17 V3.2.5 (2022-08): ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for Broadband Data Transmission Systems; Harmonised Standard for ElectroMagnetic Compatibility.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with the standard ETSI EN 301489-1, Electromagnetic compatibility and Radio spectrum Matters (ERM); Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements.



1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

WALTEK



1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission/immunity level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Charging and BT mode	Connect to the Adapter; AC230V 50Hz for adapter and BT Connect
TM2	AUX In	AUX playing
TM3	SD Card	SD Card playing
TM4	USB flash disk	USB flash disk Playing
TM5	Bluetooth	TR, CR, TT, CT for EMS testing

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	0.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
AUX Cable	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	GangQi	GQ12-050200	/
Phone	XIAOMI	MI10	/
USB flash disk	SAMSUNG	/	/
SD Card	/	/	/
Notebook	Lenovo	100-14IBD	PF0F4ABV



1.6 Performance Criteria for EMS

➤ EN 301 489-17, The performance criteria are:

- performance criteria A for immunity tests with phenomena of a continuous nature;
- performance criteria B for immunity tests with phenomena of a transient nature;
- performance criteria C for immunity tests with power interruptions exceeding a certain time.

The equipment shall meet the minimum performance criteria as specified in the following clauses.

Table 1: Performance criteria

Criteria	During test	After test
A	Shall operate as intended. (see note 1). Shall be no loss of function. Shall be no unintentional transmissions.	Shall operate as intended. Shall be no degradation of performance (see note 3). Shall be no loss of function. Shall be no loss of stored data or user programmable
B	May show loss of function (one or more). May show degradation of performance (see note 2). Shall be no unintentional transmissions.	Functions shall be self-recoverable. Shall operate as intended after recovering. Shall be no degradation of performance (see note 3). Shall be no loss of stored data or user programmable functions.
C	May be loss of function (one or more).	Functions shall be recoverable by the operator. Shall operate as intended after recovering. Shall be no degradation of performance (see note 3).



NOTE 1: Operate as intended during the test allows a level of degradation not below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

NOTE 2: Degradation of performance during the test is understood as a degradation to a level not below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

NOTE 3: No degradation of performance after the test is understood as no degradation below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. After the test no change of actual operating data or user retrievable data is allowed. If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

➤ **EN 55035, The performance criteria are:**

- A. The apparatus shall continue to operate as intended during and after the test. The manufacturer specifies some minimum performance level. The performance level may be specified by the manufacturer as a permissible loss of performance.
- B. The apparatus shall continue to operate as intended after the test. This indicates that the EUT does not need to function at normal performance levels during the test, but must recover. Again some minimal performance is defined by the manufacture. No change in operating state or loss or data is permitted.
- C. Temporary loss of function is allowed. Operation of the EUT may stop as long as it is either automatically reset or can be manually restored by operation of the controls.



1.7 Measurement Uncertainty

Measurement uncertainty	
Parameter	Uncertainty
Uncertainty for Radiated Emission in 3m chamber	@30-200MHz $\pm 4.52\text{dB}$ @0.2-1GHz $\pm 5.56\text{dB}$ @1-6GHz $\pm 3.84\text{dB}$ @6-18GHz $\pm 3.92\text{dB}$
Uncertainty for Conducted Emission	@9-150kHz $\pm 3.74\text{dB}$ @0.15-30MHz $\pm 3.34\text{dB}$
Uncertainty for Harmonic test	3.26%
Uncertainty for Flicker test	4.76%
Uncertainty for RS test	21%, k=2
Uncertainty for CS test	29%, k=2
Uncertainty for ESD test	The immunity measurement system uncertainty is within standard requirement and is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%.
Uncertainty for EFT test	
Uncertainty for Surges test	
Uncertainty for Voltage Dips, Voltage Variations and Short Interruptions Test	
Uncertainty for PFMF test	



1.8 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
☐ Chamber A: Below 1GHz					
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2023-02-25	2024-02-24
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2023-02-25	2024-02-24
Amplifier	HP	8447F	2805A03475	2023-02-25	2024-02-24
Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
Trilog Broadband Antenna	Schwarz beck	VULB9163	9163-333	2023-03-20	2026-03-19
☐ Chamber A: Above 1GHz					
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2023-02-25	2024-02-24
Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2023-02-25	2024-02-24
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2023-02-25	2024-02-24
Amplifier	C&D	PAP-1G18	14918	2023-02-25	2024-02-24
Horn Antenna	ETS	3117	00086197	2021-03-19	2024-03-18
DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
☐ Chamber B: Below 1GHz					
Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2024-04-08
Amplifier	Agilent	8447D	2944A10457	2023-02-25	2024-02-24
EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2023-02-25	2024-02-24
☒ Chamber C: Below 1GHz					
EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2024-05-27
Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
Amplifier	HP	8447F	2944A03869	2023-02-25	2024-02-24
☒ Chamber C: Above 1GHz					
EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
Amplifier	Tonscend	TAP01018050	AP22E806235	2023-02-25	2024-02-24
DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
☐ Conducted Room 1#					
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2023-02-25	2024-02-24
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2023-02-25	2024-02-24
AC LISN	Schwarz beck	NSLK8126	8126-279	2023-02-25	2024-02-24
8-WIRE ISN	Schwarz beck	8158	CAT3-8158-0059	2023-02-25	2024-02-24
8-WIRE ISN	Schwarz beck	8158	CAT5-8158-0117	2023-02-25	2024-02-24



☒ Conducted Room 2#					
EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2023-02-25	2024-02-24
LISN	Rohde & Schwarz	ENV 216	100097	2023-02-25	2024-02-24
EMF					
VDH Test Head	AFJ	VDH 30	SC022Z	2023-02-25	2024-02-24
3 Loop Antenna					
Loop Antenna	ZHINAN	ZN30401	19037	2023-02-25	2025-02-24
Clamp					
Clamp	Luthi	MDS21	3809	2023-02-27	2024-02-26
PFMF					
PMF Generator	LIONCEL	PMF-801C-C	0171101	2023-02-25	2024-02-24
PMF Antenna	LIONCEL	PMF-801C-A	0180302	2023-02-25	2024-02-24
Instantaneous PMF Generator Module	LIONCEL	PMF-801C-T	0171001	2023-02-25	2024-02-24
H/F					
Digital Power Analyzer	California Instrument	CTS	72831	2023-02-25	2024-02-24
Power Source	California Instrument	5001IX-CTS-400	60077	2023-02-25	2024-02-24
ESD					
ESD Generator	LIONCEL	ESD-203B	0170901	2023-03-14	2024-03-13
EFT/SURGE/DIPS					
Transient 2000	EMC PARTNER	TRA2000	836	2023-02-25	2024-02-24
Couple Clamp	EMC PARTNER	CN-EFT1000	513	2023-02-25	2024-02-24
CS					
CONDUCTED IMMUNITY TEST SYSTEM	FRANKONIA	CIT-10/75	126B1247/2013	2023-02-25	2024-02-24
Attenuator	EMTEST	MA-5100/6BF2	1009	2023-02-25	2024-02-24
CDN	Luthi	L-801M2/M3	2665	2023-02-25	2024-02-24
CDN	LIONCEL	CDN-T8	0210401	2023-02-25	2024-02-24
EM Clamp	TESEQ	KEMZ801A	45028	2023-02-25	2024-02-24
RS					
Signal Generator	HP	8665B	3438A00604	2023-02-25	2024-02-24
Power Sensor	Agilent	E9301A	MY52450001	2023-02-25	2024-02-24
Power Sensor	Agilent	E9304A	MY55081055	2023-02-25	2024-02-24
RF Power Amplifier	MicoTop	MPA-80-1000-250	MPA1906239	2023-02-25	2024-02-24
RF Power Amplifier	MicoTop	MPA-80-6000-100	MPA1906238	2023-02-25	2024-02-24
Antenna	SCHWARZBECK	STLP 9129	9129 114	N/A	N/A



Power Meter	Agilent	E4419B	GB42420578	2023-02-25	2024-02-24
-------------	---------	--------	------------	------------	------------

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 1#)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 2#)*	SKET	EMC-I	V2.0

*Remark: indicates software version used in the compliance certification testing.

WALTEK




2. SUMMARY OF TEST RESULTS

Standards	Reference	Description of Test Item	Result
ETSI EN 301 489-1	8.2	Radiated Emissions	Pass
	8.3	Conducted Emissions for DC Power Port	N/A
	8.4	Conducted Emissions for AC Power Port	Pass
	8.5	Harmonic Current Emissions	Pass
	8.6	Voltage Fluctuations and Flicker	Pass
	8.7	Telecommunication Ports	N/A
	9.2	Radio Frequency Electromagnetic Field	Pass
	9.3	Electrostatic Discharge	Pass
	9.4	Fast Transients, Common Mode	Pass
	9.5	Radio Frequency, Common Mode	Pass
	9.6	Transient and Surges in the Vehicular Environment	N/A
	9.7	Voltage Dips and Interruptions	Pass
	9.8	Surges	Pass
Pass: The EUT complies with the essential requirements in the standard. Fail: The EUT does not comply with the essential requirements in the standard. N/A: Not applicable.			

3.1 Test Procedure

3.2 Basic Test Setup Block Diagram




Temperature:	25 ° C
Relative Humidity:	45 %
ATM Pressure:	1015 mbar

Note: Only show the worst case in the test report




Test mode:	TM1	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	1.686MHz	31.8	9.7	41.5	56.0	-14.5	QP
2	2.810MHz	27.6	9.8	37.4	56.0	-18.6	QP
3	3.926MHz	26.5	9.8	36.3	56.0	-19.7	QP
4	9.122MHz	27.9	9.9	37.8	60.0	-22.2	QP
5	10.254MHz	34.5	9.9	44.4	60.0	-15.6	QP
6	11.002MHz	35.3	9.8	45.1	60.0	-14.9	QP
7*	562.000kHz	22.0	9.7	31.7	46.0	-14.3	AV
8*	2.822MHz	14.2	9.8	24.0	46.0	-22.0	AV
9*	5.838MHz	14.8	9.8	24.6	50.0	-25.4	AV
10*	9.194MHz	19.2	9.9	29.1	50.0	-20.9	AV
11*	10.314MHz	23.6	9.9	33.5	50.0	-16.5	AV
12*	11.038MHz	22.2	9.8	32.0	50.0	-18.0	AV




Test mode:	TM1	Polarity:	Line
------------	-----	-----------	------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	538.000kHz	32.6	9.7	42.3	56.0	-13.7	QP
2	646.000kHz	12.0	9.7	21.7	56.0	-34.3	QP
3	2.698MHz	27.4	9.9	37.3	56.0	-18.7	QP
4	7.114MHz	39.2	9.7	48.9	60.0	-11.1	QP
5	9.286MHz	40.5	9.8	50.3	60.0	-9.7	QP
6	10.406MHz	39.8	9.8	49.6	60.0	-10.4	QP
7*	546.000kHz	32.9	9.7	42.6	46.0	-3.4	AV
8*	650.000kHz	27.4	9.7	37.1	46.0	-8.9	AV
9*	1.622MHz	24.5	9.8	34.3	46.0	-11.7	AV
10*	2.726MHz	30.5	9.9	40.4	46.0	-5.6	AV
11*	5.986MHz	29.3	9.8	39.1	50.0	-10.9	AV
12*	8.186MHz	28.3	9.8	38.1	50.0	-11.9	AV




Test mode:	TM2	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	1.690MHz	32.0	9.7	41.7	56.0	-14.3	QP
2	3.906MHz	25.6	9.8	35.4	56.0	-20.6	QP
3	6.910MHz	28.4	9.8	38.2	60.0	-21.8	QP
4	8.022MHz	29.1	9.9	39.0	60.0	-21.0	QP
5	9.906MHz	36.3	9.9	46.2	60.0	-13.8	QP
6	11.442MHz	38.0	9.8	47.8	60.0	-12.2	QP
7*	1.666MHz	22.1	9.7	31.8	46.0	-14.2	AV
8*	2.746MHz	16.2	9.7	25.9	46.0	-20.1	AV
9*	3.886MHz	18.9	9.8	28.7	46.0	-17.3	AV
10*	4.994MHz	20.3	9.8	30.1	46.0	-15.9	AV
11*	10.270MHz	19.7	9.9	29.6	50.0	-20.4	AV
12*	11.390MHz	18.5	9.8	28.3	50.0	-21.7	AV




Test mode:	TM2	Polarity:	Line
------------	-----	-----------	------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	630.000kHz	17.6	9.7	27.3	56.0	-28.7	QP
2	1.642MHz	37.6	9.8	47.4	56.0	-8.6	QP
3	3.798MHz	30.3	9.9	40.2	56.0	-15.8	QP
4	8.254MHz	40.3	9.8	50.1	60.0	-9.9	QP
5	10.822MHz	37.9	9.8	47.7	60.0	-12.3	QP
6	11.542MHz	40.5	9.8	50.3	60.0	-9.7	QP
7*	550.000kHz	31.6	9.7	41.3	46.0	-4.7	AV
8*	1.646MHz	33.0	9.8	42.8	46.0	-3.2	AV
9*	2.742MHz	31.0	9.9	40.9	46.0	-5.1	AV
10*	3.826MHz	30.9	9.9	40.8	46.0	-5.2	AV
11*	8.234MHz	27.2	9.8	37.0	50.0	-13.0	AV
12*	11.914MHz	26.2	9.8	36.0	50.0	-14.0	AV




Test mode:	TM3	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	562.000kHz	33.0	9.7	42.7	56.0	-13.3	QP
2	2.790MHz	32.4	9.7	42.1	56.0	-13.9	QP
3	3.934MHz	25.3	9.8	35.1	56.0	-20.9	QP
4	10.310MHz	34.2	9.9	44.1	60.0	-15.9	QP
5	11.406MHz	33.6	9.8	43.4	60.0	-16.6	QP
6	13.066MHz	24.7	9.8	34.5	60.0	-25.5	QP
7*	558.000kHz	21.8	9.7	31.5	46.0	-14.5	AV
8*	1.674MHz	16.8	9.7	26.5	46.0	-19.5	AV
9*	2.798MHz	16.5	9.7	26.2	46.0	-19.8	AV
10*	8.774MHz	17.2	9.9	27.1	50.0	-22.9	AV
11*	9.938MHz	18.9	9.9	28.8	50.0	-21.2	AV
12*	11.434MHz	24.3	9.8	34.1	50.0	-15.9	AV




Test mode:	TM3	Polarity:	Line
------------	-----	-----------	------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	1.630MHz	31.4	9.8	41.2	56.0	-14.8	QP
2	2.782MHz	26.5	9.9	36.4	56.0	-19.6	QP
3	3.862MHz	39.6	9.9	49.5	56.0	-6.5	QP
4	8.258MHz	35.9	9.8	45.7	60.0	-14.3	QP
5	10.074MHz	37.2	9.8	47.0	60.0	-13.0	QP
6	11.106MHz	30.4	9.8	40.2	60.0	-19.8	QP
7*	1.654MHz	31.5	9.8	41.3	46.0	-4.7	AV
8*	2.754MHz	29.7	9.9	39.6	46.0	-6.4	AV
9*	3.854MHz	29.9	9.9	39.8	46.0	-6.2	AV
10*	7.158MHz	27.4	9.7	37.1	50.0	-12.9	AV
11*	8.254MHz	29.1	9.8	38.9	50.0	-11.1	AV
12*	10.086MHz	26.8	9.8	36.6	50.0	-13.4	AV




Test mode:	TM4	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	550.000kHz	30.9	9.7	40.6	56.0	-15.4	QP
2	2.734MHz	17.9	9.7	27.6	56.0	-28.4	QP
3	3.870MHz	41.6	9.8	51.4	56.0	-4.6	QP
4	7.190MHz	23.5	9.8	33.3	60.0	-26.7	QP
5	9.390MHz	31.5	9.9	41.4	60.0	-18.6	QP
6	10.858MHz	36.3	9.8	46.1	60.0	-13.9	QP
7*	550.000kHz	21.1	9.7	30.8	46.0	-15.2	AV
8*	2.762MHz	22.0	9.7	31.7	46.0	-14.3	AV
9*	3.862MHz	20.9	9.8	30.7	46.0	-15.3	AV
10*	7.174MHz	18.7	9.8	28.5	50.0	-21.5	AV
11*	9.386MHz	19.6	9.9	29.5	50.0	-20.5	AV
12*	11.958MHz	19.5	9.8	29.3	50.0	-20.7	AV



Test mode:	TM4	Polarity:	Line
------------	-----	-----------	------




No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector
1	650.000kHz	13.3	9.7	23.0	56.0	-33.0	QP
2	1.626MHz	32.6	9.8	42.4	56.0	-13.6	QP
3	2.714MHz	31.9	9.9	41.8	56.0	-14.2	QP
4	7.394MHz	19.0	9.7	28.7	60.0	-31.3	QP
5	8.418MHz	30.9	9.8	40.7	60.0	-19.3	QP
6	11.018MHz	26.9	9.8	36.7	60.0	-23.3	QP
7*	646.000kHz	28.1	9.7	37.8	46.0	-8.2	AV
8*	1.646MHz	31.9	9.8	41.7	46.0	-4.3	AV
9*	2.718MHz	25.4	9.9	35.3	46.0	-10.7	AV
10*	3.794MHz	23.1	9.9	33.0	46.0	-13.0	AV
11*	5.586MHz	22.7	9.8	32.5	50.0	-17.5	AV
12*	6.662MHz	23.5	9.7	33.2	50.0	-16.8	AV



4. Radiated Emissions

4.1 Test Procedure

Test is conducting under the description of EN55032 Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement.



4.2 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{EN 301489 Class B Limit}$$



4.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

4.4 Summary of Test Results/Plots

Note: Only show the worst case in the test report

➤ 30MHz to 1GHz


Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.1581	29.76	-8.48	21.28	40.00	-18.72	-	-	QP
2	68.7450	28.96	-10.54	18.42	40.00	-21.58	-	-	QP
3	173.8146	38.68	-9.42	29.26	40.00	-10.74	-	-	QP
4	278.3308	32.14	-9.00	23.14	47.00	-23.86	-	-	QP
5	421.3287	32.27	-5.38	26.89	47.00	-20.11	-	-	QP
6	744.4265	30.92	-0.27	30.65	47.00	-16.35	-	-	QP




Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	74.2696	33.71	-11.70	22.01	40.00	-17.99	-	-	QP
2	107.0306	34.44	-11.85	22.59	40.00	-17.41	-	-	QP
3	171.3890	33.73	-9.08	24.65	40.00	-15.35	-	-	QP
4	227.0164	33.58	-11.76	21.82	40.00	-18.18	-	-	QP
5	421.3287	33.31	-5.38	27.93	47.00	-19.07	-	-	QP
6	637.7947	32.34	-1.36	30.98	47.00	-16.02	-	-	QP




Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.8172	29.82	-8.17	21.65	40.00	-18.35	-	-	QP
2	74.2696	29.73	-11.70	18.03	40.00	-21.97	-	-	QP
3	173.8146	39.23	-9.42	29.81	40.00	-10.19	-	-	QP
4	261.2730	34.55	-9.71	24.84	47.00	-22.16	-	-	QP
5	401.1050	37.46	-5.93	31.53	47.00	-15.47	-	-	QP
6	744.4265	30.77	-0.27	30.50	47.00	-16.50	-	-	QP




Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	82.5257	35.69	-13.00	22.69	40.00	-17.31	-	-	QP
2	107.0306	34.29	-11.85	22.44	40.00	-17.56	-	-	QP
3	165.4716	33.45	-8.76	24.69	40.00	-15.31	-	-	QP
4	278.3308	33.65	-9.00	24.65	47.00	-22.35	-	-	QP
5	421.3287	36.13	-5.38	30.75	47.00	-16.25	-	-	QP
6	660.6025	33.45	-1.28	32.17	47.00	-14.83	-	-	QP




Test mode:	TM3	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.9081	28.86	-8.72	20.14	40.00	-19.86	-	-	QP
2	58.4855	29.72	-8.84	20.88	40.00	-19.12	-	-	QP
3	147.8747	30.51	-8.77	21.74	40.00	-18.26	-	-	QP
4	381.8520	29.55	-6.33	23.22	47.00	-23.78	-	-	QP
5	607.1806	30.63	-1.64	28.99	47.00	-18.01	-	-	QP
6	875.0133	32.63	0.97	33.60	47.00	-13.40	-	-	QP




Test mode:	TM3	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	47.0371	28.63	-8.32	20.31	40.00	-19.69	-	-	QP
2	86.0795	35.94	-13.04	22.90	40.00	-17.10	-	-	QP
3	151.0252	32.63	-8.61	24.02	40.00	-15.98	-	-	QP
4	227.0164	33.19	-11.76	21.43	40.00	-18.57	-	-	QP
5	395.5071	31.26	-6.05	25.21	47.00	-21.79	-	-	QP
6	660.6025	31.49	-1.28	30.21	47.00	-16.79	-	-	QP




Test mode:	TM4	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.4483	28.51	-8.48	20.03	40.00	-19.97	-	-	QP
2	67.7856	29.54	-10.36	19.18	40.00	-20.82	-	-	QP
3	148.9175	29.97	-8.68	21.29	40.00	-18.71	-	-	QP
4	231.8531	30.97	-11.43	19.54	47.00	-27.46	-	-	QP
5	433.3397	30.70	-5.05	25.65	47.00	-21.35	-	-	QP
6	827.1795	31.95	0.54	32.49	47.00	-14.51	-	-	QP



Test mode:	TM4	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.7811	30.63	-9.17	21.46	40.00	-18.54	-	-	QP
2	57.6693	30.05	-8.79	21.26	40.00	-18.74	-	-	QP
3	89.7866	35.56	-13.10	22.46	40.00	-17.54	-	-	QP
4	165.4716	31.94	-8.76	23.18	40.00	-16.82	-	-	QP
5	309.2710	30.97	-8.00	22.97	47.00	-24.03	-	-	QP
6	655.9766	32.42	-1.30	31.12	47.00	-15.88	-	-	QP



➤ Above 1GHz


Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1196.661	56.96	-23.75	33.21	74.00	-40.79	-	-	peak
2	1196.661	43.73	-23.75	19.98	54.00	-34.02	-	-	AVG
3	1484.350	56.35	-22.67	33.68	74.00	-40.32	-	-	peak
4	1516.676	44.43	-22.52	21.91	54.00	-32.09	-	-	AVG
5	1874.557	56.76	-20.37	36.39	74.00	-37.61	-	-	peak
6	1908.516	44.22	-20.17	24.05	54.00	-29.95	-	-	AVG
7	2627.147	55.63	-18.39	37.24	74.00	-36.76	-	-	peak
8	2627.147	43.21	-18.39	24.82	54.00	-29.18	-	-	AVG
9	3476.316	44.34	-14.36	29.98	54.00	-24.02	-	-	AVG
10	3830.219	57.55	-14.58	42.97	74.00	-31.03	-	-	peak
11	4889.498	66.15	-12.54	53.61	74.00	-20.39	-	-	peak
12	4889.498	47.99	-12.54	35.45	54.00	-18.55	-	-	AVG




Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1117.743	57.07	-24.40	32.67	74.00	-41.33	-	-	peak
2	1121.764	44.77	-24.37	20.40	54.00	-33.60	-	-	AVG
3	1538.617	56.18	-22.37	33.81	74.00	-40.19	-	-	peak
4	1544.152	44.23	-22.33	21.90	54.00	-32.10	-	-	AVG
5	1894.859	44.25	-20.25	24.00	54.00	-30.00	-	-	AVG
6	1999.716	56.96	-19.63	37.33	74.00	-36.67	-	-	peak
7	2646.081	56.89	-18.36	38.53	74.00	-35.47	-	-	peak
8	2694.017	43.32	-18.26	25.06	54.00	-28.94	-	-	AVG
9	3695.127	44.38	-14.42	29.96	54.00	-24.04	-	-	AVG
10	3998.864	61.88	-14.79	47.09	74.00	-26.91	-	-	peak
11	4889.498	72.01	-12.54	59.47	74.00	-14.53	-	-	peak
12	4889.498	51.16	-12.54	38.62	54.00	-15.38	-	-	AVG




Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1133.913	57.03	-24.26	32.77	74.00	-41.23	-	-	peak
2	1142.085	44.53	-24.20	20.33	54.00	-33.67	-	-	AVG
3	1500.426	56.13	-22.62	33.51	74.00	-40.49	-	-	peak
4	1533.102	44.31	-22.40	21.91	54.00	-32.09	-	-	AVG
5	1915.381	56.42	-20.13	36.29	74.00	-37.71	-	-	peak
6	2156.335	42.51	-19.32	23.19	54.00	-30.81	-	-	AVG
7	2617.730	55.11	-18.41	36.70	74.00	-37.30	-	-	peak
8	3032.922	42.79	-17.41	25.38	54.00	-28.62	-	-	AVG
9	3451.440	57.69	-14.52	43.17	74.00	-30.83	-	-	peak
10	4027.685	44.17	-14.69	29.48	54.00	-24.52	-	-	AVG
11	4889.498	66.95	-12.54	54.41	74.00	-19.59	-	-	peak
12	4889.498	48.32	-12.54	35.78	54.00	-18.22	-	-	AVG




Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1089.999	56.31	-24.62	31.69	74.00	-42.31	-	-	peak
2	1154.455	44.60	-24.10	20.50	54.00	-33.50	-	-	AVG
3	1452.713	55.36	-22.76	32.60	74.00	-41.40	-	-	peak
4	1511.240	44.43	-22.55	21.88	54.00	-32.12	-	-	AVG
5	1894.859	57.36	-20.25	37.11	74.00	-36.89	-	-	peak
6	1915.381	44.08	-20.13	23.95	54.00	-30.05	-	-	AVG
7	2684.361	43.41	-18.27	25.14	54.00	-28.86	-	-	AVG
8	2694.017	56.37	-18.26	38.11	74.00	-35.89	-	-	peak
9	3708.419	44.47	-14.44	30.03	54.00	-23.97	-	-	AVG
10	3998.864	60.92	-14.79	46.13	74.00	-27.87	-	-	peak
11	4889.498	71.48	-12.54	58.94	74.00	-15.06	-	-	peak
12	4889.498	51.14	-12.54	38.60	54.00	-15.40	-	-	AVG




Test mode:	TM3	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1154.455	56.46	-24.10	32.36	74.00	-41.64	-	-	peak
2	1154.455	44.48	-24.10	20.38	54.00	-33.62	-	-	AVG
3	1500.426	44.35	-22.62	21.73	54.00	-32.27	-	-	AVG
4	1566.490	55.46	-22.20	33.26	74.00	-40.74	-	-	peak
5	2187.529	55.51	-19.27	36.24	74.00	-37.76	-	-	peak
6	2203.295	43.17	-19.23	23.94	54.00	-30.06	-	-	AVG
7	2617.730	54.96	-18.41	36.55	74.00	-37.45	-	-	peak
8	3076.797	42.91	-17.12	25.79	54.00	-28.21	-	-	AVG
9	3629.379	56.67	-14.35	42.32	74.00	-31.68	-	-	peak
10	4159.971	43.78	-14.25	29.53	54.00	-24.47	-	-	AVG
11	4889.498	64.66	-12.54	52.12	74.00	-21.88	-	-	peak
12	4889.498	46.87	-12.54	34.33	54.00	-19.67	-	-	AVG




Test mode:	TM3	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1117.743	56.77	-24.40	32.37	74.00	-41.63	-	-	peak
2	1142.085	44.62	-24.20	20.42	54.00	-33.58	-	-	AVG
3	1538.617	44.29	-22.37	21.92	54.00	-32.08	-	-	AVG
4	1544.152	56.28	-22.33	33.95	74.00	-40.05	-	-	peak
5	2211.221	43.28	-19.22	24.06	54.00	-29.94	-	-	AVG
6	2275.661	56.65	-19.09	37.56	74.00	-36.44	-	-	peak
7	3076.797	55.36	-17.12	38.24	74.00	-35.76	-	-	peak
8	3235.421	43.79	-16.01	27.78	54.00	-26.22	-	-	AVG
9	3681.883	44.36	-14.41	29.95	54.00	-24.05	-	-	AVG
10	3998.864	60.02	-14.79	45.23	74.00	-28.77	-	-	peak
11	4889.498	72.01	-12.54	59.47	74.00	-14.53	-	-	peak
12	4889.498	51.14	-12.54	38.60	54.00	-15.40	-	-	AVG




Test mode:	TM4	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1150.317	56.87	-24.13	32.74	74.00	-41.26	-	-	peak
2	1166.958	44.20	-24.00	20.20	54.00	-33.80	-	-	AVG
3	1516.676	44.24	-22.52	21.72	54.00	-32.28	-	-	AVG
4	1533.102	56.60	-22.40	34.20	74.00	-39.80	-	-	peak
5	1929.186	56.45	-20.05	36.40	74.00	-37.60	-	-	peak
6	1943.090	43.88	-19.97	23.91	54.00	-30.09	-	-	AVG
7	2636.597	55.95	-18.37	37.58	74.00	-36.42	-	-	peak
8	2684.361	43.16	-18.27	24.89	54.00	-29.11	-	-	AVG
9	3668.686	44.26	-14.39	29.87	54.00	-24.13	-	-	AVG
10	3748.582	57.27	-14.49	42.78	74.00	-31.22	-	-	peak
11	4889.498	66.26	-12.54	53.72	74.00	-20.28	-	-	peak
12	4889.498	48.05	-12.54	35.51	54.00	-18.49	-	-	AVG



Test mode:	TM4	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	1218.339	56.31	-23.65	32.66	74.00	-41.34	-	-	peak
2	1218.339	43.66	-23.65	20.01	54.00	-33.99	-	-	AVG
3	1516.676	57.55	-22.52	35.03	74.00	-38.97	-	-	peak
4	1533.102	44.26	-22.40	21.86	54.00	-32.14	-	-	AVG
5	1915.381	44.11	-20.13	23.98	54.00	-30.02	-	-	AVG
6	1957.094	56.62	-19.88	36.74	74.00	-37.26	-	-	peak
7	2617.730	55.63	-18.41	37.22	74.00	-36.78	-	-	peak
8	2665.152	43.56	-18.32	25.24	54.00	-28.76	-	-	AVG
9	3463.856	44.57	-14.44	30.13	54.00	-23.87	-	-	AVG
10	3998.864	59.82	-14.79	45.03	74.00	-28.97	-	-	peak
11	4889.498	72.29	-12.54	59.75	74.00	-14.25	-	-	peak
12	4889.498	51.50	-12.54	38.96	54.00	-15.04	-	-	AVG

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.



5. Harmonic Current Emissions

5.1 Test Setup Block Diagram



5.2 Test Standards

EN IEC 61000-3-2, Clause 7.2 Limits for Class A equipment.

5.3 Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	1015 mbar

5.4 Harmonic Current Emissions Test Data



Harmonics – Class-A

Test category: Class-A (European limits)

Test Margin: 100

Test date: 2023/12/19

Start time: 15:33:12

End time: 15:35:53


Test duration (min): 2.5

Data file name: H-000442.cts_data

Test Result: Pass


Source qualification: Normal

Current & voltage waveforms



Harmonics and Class A limit line

European Limits

**Test result: Pass Worst harmonics H17-6.4% of 150% limit, H15-9.6% of 100% limit**



Current Test Result Summary (Run time)

Test category: Class-A (European limits)

Test Margin: 100

Test date: 2023/12/19

Start time: 15:33:12

End time: 15:35:53

Test duration (min): 2.5

Data file name: H-000442.cts_data

Test Result: Pass

Source qualification: Normal

THC(A): 0.055

I-THD(%): 227.7

POHC(A): 0.014

POHC Limit(A): 0.251

Highest parameter values during test:

V_RMS (Volts): 230.03

Frequency(Hz): 50.00

I_Peak (Amps): 0.330

I_RMS (Amps): 0.066

I_Fund (Amps): 0.024

Crest Factor: 5.045

Power (Watts): 5.5

Power Factor: 0.369

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.001	1.080	N/A	0.001	1.620	N/A	Pass
3	0.022	2.300	1.0	0.023	3.450	0.7	Pass
4	0.001	0.430	N/A	0.001	0.645	N/A	Pass
5	0.021	1.140	1.9	0.021	1.710	1.3	Pass
6	0.000	0.300	N/A	0.001	0.450	N/A	Pass
7	0.020	0.770	2.6	0.021	1.155	1.8	Pass
8	0.000	0.230	N/A	0.001	0.345	N/A	Pass
9	0.019	0.400	4.8	0.019	0.600	3.2	Pass
10	0.000	0.184	N/A	0.001	0.276	N/A	Pass
11	0.018	0.330	5.4	0.018	0.495	3.6	Pass
12	0.000	0.153	N/A	0.001	0.230	N/A	Pass
13	0.016	0.210	7.7	0.016	0.315	5.2	Pass
14	0.000	0.131	N/A	0.001	0.197	N/A	Pass
15	0.014	0.150	9.6	0.015	0.225	6.4	Pass
16	0.000	0.115	N/A	0.001	0.173	N/A	Pass
17	0.013	0.132	9.5	0.013	0.198	6.4	Pass
18	0.000	0.102	N/A	0.001	0.153	N/A	Pass
19	0.011	0.118	9.0	0.011	0.178	6.1	Pass
20	0.000	0.092	N/A	0.001	0.138	N/A	Pass
21	0.009	0.107	8.3	0.009	0.161	5.6	Pass
22	0.000	0.084	N/A	0.001	0.125	N/A	Pass
23	0.007	0.098	7.3	0.007	0.147	5.0	Pass
24	0.000	0.077	N/A	0.000	0.115	N/A	Pass
25	0.006	0.090	6.2	0.006	0.135	4.2	Pass
26	0.000	0.071	N/A	0.000	0.107	N/A	Pass
27	0.004	0.083	N/A	0.004	0.125	N/A	Pass



Reference No.: WTF23X12257064W003

28	0.000	0.066	N/A	0.000	0.099	N/A	Pass
29	0.003	0.078	N/A	0.003	0.116	N/A	Pass
30	0.000	0.061	N/A	0.000	0.092	N/A	Pass
31	0.002	0.073	N/A	0.002	0.109	N/A	Pass
32	0.000	0.058	N/A	0.000	0.086	N/A	Pass
33	0.002	0.068	N/A	0.002	0.102	N/A	Pass
34	0.000	0.054	N/A	0.000	0.081	N/A	Pass
35	0.002	0.064	N/A	0.002	0.096	N/A	Pass
36	0.000	0.051	N/A	0.000	0.077	N/A	Pass
37	0.002	0.061	N/A	0.002	0.091	N/A	Pass
38	0.000	0.048	N/A	0.000	0.073	N/A	Pass
39	0.002	0.058	N/A	0.002	0.087	N/A	Pass
40	0.000	0.046	N/A	0.000	0.069	N/A	Pass

WALTEK

**Voltage Source Verification Data (Run time)**

Test category: Class-A (European limits)

Test Margin: 100

Test date: 2023/12/19

Start time: 15:33:12

End time: 15:35:53

Test duration (min): 2.5

Data file name: H-000442.cts_data

Test Result: Pass

Source qualification: Normal

Highest parameter values during test:

Voltage (Vrms): 230.03

Frequency(Hz): 50.00

I_Peak (Amps): 0.330

I_RMS (Amps): 0.066

I_Fund (Amps): 0.024

Crest Factor: 5.045

Power (Watts): 5.5

Power Factor: 0.369

Harm#	Harmonics V-rms	Limit V-rms	% of Limit	Status
2	0.051	0.460	11.19	OK
3	0.499	2.070	24.13	OK
4	0.086	0.460	18.80	OK
5	0.057	0.920	6.24	OK
6	0.031	0.460	6.69	OK
7	0.019	0.690	2.72	OK
8	0.020	0.460	4.27	OK
9	0.018	0.460	3.87	OK
10	0.010	0.460	2.08	OK
11	0.016	0.230	7.04	OK
12	0.014	0.230	5.98	OK
13	0.020	0.230	8.60	OK
14	0.005	0.230	2.32	OK
15	0.013	0.230	5.78	OK
16	0.008	0.230	3.60	OK
17	0.016	0.230	6.98	OK
18	0.011	0.230	4.84	OK
19	0.019	0.230	8.14	OK
20	0.015	0.230	6.57	OK
21	0.016	0.230	7.13	OK
22	0.004	0.230	1.56	OK
23	0.012	0.230	5.31	OK
24	0.004	0.230	1.86	OK
25	0.010	0.230	4.30	OK
26	0.004	0.230	1.63	OK
27	0.005	0.230	2.08	OK
28	0.005	0.230	2.17	OK



Reference No.: WTF23X12257064W003


29	0.011	0.230	4.66	OK
30	0.004	0.230	1.53	OK
31	0.007	0.230	2.89	OK
32	0.004	0.230	1.56	OK
33	0.007	0.230	3.10	OK
34	0.003	0.230	1.16	OK
35	0.004	0.230	1.84	OK
36	0.003	0.230	1.41	OK
37	0.004	0.230	1.76	OK
38	0.003	0.230	1.24	OK
39	0.004	0.230	1.80	OK
40	0.008	0.230	3.62	OK

WALTEK



6. Voltage Fluctuation and Flicker

6.1 Test Setup Block Diagram



6.2 Test Standards

EN 61000-3-3, Limit: Clause 5.

6.3 Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	1015 mbar

6.4 Voltage Fluctuation and Flicker Test Data




Test mode:	TM1(worst case)
------------	-----------------

Test Result: Pass


Status: Test Completed

Pst and limit line

European Limits



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt): 229.91

Highest dt (%):

T-max (mS): 0

Highest dc (%): 0.00

Highest dmax (%): 0.00

Highest Pst (10 min. period): 0.230

Highest Plt (2 hr. period): 0.101

Test limit (%):

Test limit (mS): 500.0 Pass

Test limit (%): 3.30 Pass

Test limit (%): 4.00 Pass


Test limit: 1.000 Pass

Test limit: 0.650 Pass



7. Electrostatic Discharge (ESD)

7.1 Test Setup Block Diagram



7.2 Test Performance

Required Performance Criterion:	B
Mode:	TM1-TM5
Note: TM5 for TT, TR	

7.3 Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

7.4 Electrostatic Discharge Immunity Test Data



Test mode	TM1-TM5							
Test Points	Test Levels (kV)							
	-2	+2	-4	+4	-6	+6	-8	+8
Air Discharge								
USB Port	A	A	A	A	A	A	A	A
Gap	A	A	A	A	A	A	A	A
Button	A	A	A	A	A	A	A	A
Enclosure	A	A	A	A	A	A	A	A
Direct Contact Discharge								
USB Port	A	A	A	A	/	/	/	/
Indirect Contact Discharge								
HCP (6 Sides)	A	A	A	A	/	/	/	/
VCP (4 Sides)	A	A	A	A	/	/	/	/


Test Result: Pass

WALTEK



8. Radio Frequency Electromagnetic Field (R/S)

8.1 Test Setup Block Diagram



8.2 Test Performance

Required Performance Criterion:	A
Mode:	TM1-TM5
Note: TM5 for CT,CR	

8.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1010 mbar

8.4 Continuous Radiated Disturbances Test Data

Frequency step: 1% of fundamental
Dwell time: 1 second
Modulation: AM by 1kHz sine wave with 80% modulation depth



Test mode		TM1-TM5							
Frequency Range(MHz)	Field (V/m)	Front		Rear		Left Side		Right Side	
		VERT	HORI	VERT	HORI	VERT	HORI	VERT	HORI
80-1000	3	A	A	A	A	A	A	A	A
1000-3000	3	A	A	A	A	A	A	A	A
3000-6000	3	A	A	A	A	A	A	A	A

Test Result: Pass


WALTEK




9. Fast Transients, Common Mode (EFT)

9.1 Test Setup Block Diagram

For AC Mains or DC Ports:



For Signal or Telecommunication Ports:



9.2 Test Performance

Required Performance Criterion:	B
Mode:	TM1-TM5
Note:TM5 for TT,TR	

9.3 Environmental Conditions

Temperature:	22 °C
Relative Humidity:	53%
ATM Pressure:	1011 mbar

9.4 Electrical Fast Transients Test Data



Test Mode		TM1-TM5							
Test Line		Test Levels (kV)							
		+0.5	-0.5	+1.0	-1.0	+2.0	-2.0	+4.0	-4.0
AC Main Power port	L	A	A	A	A	/	/	/	/
	N	A	A	A	A	/	/	/	/
	PE	/	/	/	/	/	/	/	/
	L-N	A	A	A	A	/	/	/	/
	L-PE	/	/	/	/	/	/	/	/
	N-PE	/	/	/	/	/	/	/	/
	L-N-PE	/	/	/	/	/	/	/	/
Signal ports	/	/	/	/	/	/	/	/	/

Test Result: Pass


WALTEK




10. Surges

10.1 Test Setup Block Diagram

For AC Mains or DC Ports:



For Signal or Telecommunication Ports:



10.2 Test Performance

Required Performance Criterion:	B
Mode:	TM1-TM5
Note:TM5 for TT,TR	

10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1011 mbar

10.4 Surge Test Data



Test Mode	TM1-TM5			
Voltage	Poll	Path	Pass	Fail
0.5kV	±	L-N	A	/
1kV	±	L-N	A	/
2kV	±	L-N, L-PE, N-PE	/	/
4kV	±	L-N, L-PE, N-PE	/	/

Test Result: Pass


WALTEK




11. Radio Frequency, Common Mode (C/S)

11.1 Test Setup Block Diagram

For AC Mains or DC Input:



For Signal or Telecommunication Ports:



11.2 Test Performance

Required Performance Criterion:	A
Mode:	TM1-TM5
Note: TM5 for CT,CR	

11.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1011 mbar

11.4 Continuous Conducted Disturbances Test Data

Sweep frequency range: 150kHz~80MHz
Frequency step: 1% of fundamental
Dwell time: 1 second



Test Mode		TM1-TM5		
Level	Voltage (V) (rms, unmodulated)	Modulation:	Pass	Fail
1	1	AM 80%, 1kHz sinewave	/	/
2	3	AM 80%, 1kHz sinewave	A	/
3	10	AM 80%, 1kHz sinewave	/	/
X	Special	/	/	/


Test Result: Pass

WALTEK



12. Voltage Dips and Interruptions

12.1 Test Setup Block Diagram



12.2 Test Performance

Required Performance Criterion:	B for voltage dip/ C for voltage interruption
Mode:	TM1-TM5
Note: TM5 for TT, TR	

12.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50%
ATM Pressure:	1011 mbar

12.4 Voltage Dips And Interruptions Test Data

U: Voltage dips in % U_T (U_T is rated voltage for the EUT)

T: Test duration

Level	U	T	Phase Angle	N	Pass	Fail
1	100%	10ms	0/90/180/270	3	A	/
2	100%	20ms	0/90/180/270	3	B	/
3	30%	500ms	0/90/180/270	3	B	/
4	100%	5000ms	0/90/180/270	3	C	/

Test Result: Pass



EXHIBIT 1 - EUT PHOTOGRAPHS

Please refer to “ANNEX”.

WALTEK




EXHIBIT 2 - TEST SETUP PHOTOGRAPHS

**Conducted Emission
Test Setup**




**Radiation Emission
Test View(30MHz to
1GHz)**






**Radiation Emission
Test Setup (Above
1GHz)**




**Harmonic/Flicker Test
View**






ESD Test View




R/S Test View





EFT/ Surges/ Dips and
Interruptions Test View



CS Test View



***** END OF REPORT *****