

EMC Test Report

Report No.: AGC05443240905EE01

PRODUCT DESIGNATION: Bamboo torch with keyring

BRAND NAME : N/A

MODEL NAME : M06894

APPLICANT: MID OCEAN BRANDS B.V.

DATE OF ISSUE : Sep. 11, 2024

STANDARD(S) : EN IEC 55015:2019/A11:2020

EN IEC 61547:2023

REPORT VERSION: V1.0

Attestation of Global Configuration (Shenzhen) Co., Ltd



Page 2 of 31

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	1	Sep. 11, 2024	Valid	Initial release







Table of contents

1. (General information	5
2. I	Description of Test Configuration	е
	2.1. Technical Description of Product	6
	2.2. Description of Support Equipment	6
	2.3. Description of Test Modes	6
3. \$	Summary of Measurement Results and Uncertainty	7
	3.1. Test Specifications	7
	3.2. Description of Measurement Results	7
	3.3. Description of Measurement Uncertainty	9
4.	Test Facility	10
5. I	Measurement of Radiated Emissions at Frequencies up to 1 GHz	11
	5.1. Requirements	11
	5.2. Block Diagram of Test Setup	11
	5.3. Equipment Details	12
	5.4. Configuration of the EUT and method of measurement	12
	5.5. Test Summary	13
6. I	Measurement of Electrostatic discharge	15
	6.1. Requirements	15
	6.2. Block Diagram of Test Setup	15
	6.3. Equipment Details	16
	6.4. Configuration of the EUT and method of measurement	16
	6.5. Test Summary	17
7. I	Measurement of Radio-Frequency Electromagnetic Field	18
	7.1. Requirements	18
	7.2. Block Diagram of Test Setup	19
	7.3. Equipment Details	20
	7.4. Configuration of the EUT and method of measurement	20
	7.5. Test Summary	21
8. I	Measurement of Power Frequency Magnetic Field	22
	8.1. Requirements	22
	8.2. Block Diagram of Test Setup	22
	8.3. Equipment Details	23
	8.4. Configuration of the EUT and method of measurement	23



Report No.: AGC05443240905EE01 Page 4 of 31

8.5. Test Summary	24
9. Photographs of Test Setup	
10. Photographs of EUT	27





1. General information

Tr Gonoral Information	
Applicant	MID OCEAN BRANDS B.V.
Address	7/F. Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Manufacturer	MID OCEAN BRANDS B.V.
Address	7/F. Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Factory	MID OCEAN BRANDS B.V.
Address	7/F. Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Product Designation	Bamboo torch with keyring
Brand Name	N/A
Test Model	MO6894
Series Model(s)	N/A
Difference Description	N/A
Deviation from Standard	No any deviation from the test method
Date of receipt of test item	Sep. 05, 2024
Date of Test	Sep. 05, 2024 to Sep. 11, 2024
Test Result	Pass
Test Report Form No	AGCER-EMC-GEN-V1
Note: The test results of th	is report relate only to the tested sample identified in this report.

Prepared By	Jouk Gai	
	Jack Gui (Project Engineer)	Sep. 11, 2024
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Sep. 11, 2024
Approved By	Max Zhang	
	Max Zhang (Authorized Officer)	Sep. 11, 2024




Page 6 of 31

2. Description of Test Configuration

2.1. Technical Description of Product

Categorization of Equipment	Class B equipment
Test arrangements of EUT	Table-top
Hardware Version	N/A
Software Version	N/A
Highest Internal Frequency	Less than 108MHz
EUT Input Rating	DC 4.5V
Adapter Information	N/A
Battery Information	N/A

Connection Diagram of Host System



I/O Port Information (⊠ Applicable ☐ Not Applicable)

Port Type	Input/Output	Number	Cable Description
DC power	ln	1	

2.2. Description of Support Equipment

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
-					

2.3. Description of Test Modes

No	Test Mode Description	Worst
1	Lighting mode	



Page 7 of 31

3. Summary of Measurement Results and Uncertainty

3.1. Test Specifications

EN IEC 55015:2019/A11:2020	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN IEC 61547:2023	Equipment for general lighting purposes - EMC immunity requirements

3.2. Description of Measurement Results

Test items	Test Standard(s)	Verdict
Radiated emissions at frequencies up to 1 GHz	EN IEC 55015	Pass
Electrostatic discharge	IEC 61000-4-2 a	Pass
Radio-frequency electromagnetic field	IEC 61000-4-3 a	Pass
Power-frequency magnetic field	IEC 61000-4-8 a	Pass
N. (

Note:

a. The applicable versions of the basic standards are defined in the standard which listed in the test specification.



Page 8 of 31

Performance table

	Performance Criteria for Immunity
Performance	During the test, no change of the luminous intensity shall be observed and the regulating
criterion A	control, if any, shall operate during the test as intended.
Performance criterion B	During the test, the luminous intensity may change to any value. After the test, the luminous intensity shall be restored to its initial value within 1 min (30 min for high pressure gas discharge lamps). Regulating controls need not function during the test, but after the test, the mode of the control shall be the same as before the test, provided that during the test no mode changing commands were given.
Performance	During and after the test, any change of the luminous intensity is allowed and the light source(s)
renomance	may be extinguished. After the test, within 30 min, all functions shall return to normal, if
criterion C	necessary by temporary interruption of the mains supply and/or operating the regulating control.
The fellowing	

The following additional requirement applies to lighting equipment incorporating a starting device: after the test, the lighting equipment is switched off for 30 min and back on again. The lighting equipment shall start and operate as intended.



Page 9 of 31

3.3. Description of Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%

Item	Measurement Uncertainty	
Radiated emissions at frequencies up to 1 GHz	Uc = ±3.9 dB	



Page 10 of 31

4. Test Facility

Laboratory name: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Laboratory Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laborat ories (CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This laboratory also meets the requirements of any additional program requirements in the Electrical field.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

CAB identifier: CN0063

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

VCCI Membership No.: 4112

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered in accordance with VCCI Council Rules.

VCCI Registration No. C-20098 for conducted emissions at AC main power ports

VCCI Registration No. T-20102 for conducted emissions at telecommunication ports

VCCI Registration No. R-20136 for radiated emissions below 1GHz

VCCI Registration No. G-20132 for radiated emissions above 1GHz



Page 11 of 31

5. Measurement of Radiated Emissions at Frequencies up to 1 GHz


5.1. Requirements

Requirements for radiated emissions at frequencies up to 1 GHz at 3m distance

Test facility	Detector type/ bandwidth	Frequency Range (MHz)	Limits dB(µV/m)	Measurement specifications
SAC Quasi-peak/ 120kHz		30 to 230	40	Instrumentation: CISPR 16-1-1, Clauses 4, 5 Antennas: CISPR 16-1-4, Clause 4.5
		230 to 1000	47	Test Site: CISPR 16-1-4, Clause 6 Method: CISPR 16-2-3, Clause 7.6

Note:

5.2. Block Diagram of Test Setup



^{1.} The lower limit shall apply at the transition frequency.



Page 12 of 31

5.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 01, 2024	Jan. 31, 2025
Antenna	SCHWARZBECK	VULB9168	D69250	May 11, 2023	May 10, 2025
Attenuator	East sheep	LM-XX-6-5W	N/A	Jun. 09, 2023	Jun. 08, 2025

Measuring Software

Software Name	Manufacturer	Details	
EZ-EMC	FARA	For EMC Measurement, Version RA-03A	

5.4. Configuration of the EUT and method of measurement


- a. The EUT was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, the EUT was placed on the top surface of a measurement table, 0.8 m high from the horizontal reference plane. When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 10 cm non-conductive covering to insulate the EUT from the ground plane.
- b. Support equipment, if needed, was placed as per CISPR 16-2-3.
- c. All I/O cables were positioned to simulate typical actual usage as per CISPR 16-2-3.
- d. The maximum receiving level of radiated emissions from the EUT was measured while the turntable was rotated from 0° to 360° and the antenna height was scanned between 1 m and 4 m. The cables were laid out to attain the maximum level of radiated emissions.
- e. The more description of the tests, the test methods, and the test set-ups are given in the applicable test standard.
- f. Record at least six highest emissions relative to the limits at each frequency of interest unless the emission is 10 dB or greater below the limit.
- g. A radiated emission is calculated by the following equation:
 - Measurement Level dB(μV/m) = Receiver reading dB(μV) + Factor(dB/m)
 - Factor(dB/m) = Antenna Factor(dB/m) + Cable Loss(dB)
 - Margin= Limit-Level



Report No.: AGC05443240905EE01 Page 13 of 31


5.5. Test Summary


Test Engineer	Carpe Lin	Temperature	22.8℃
Test Date	2024-09-07	Air Pressure	985 Mbar
Worst Mode	Mode 1	Relative Humidity	58.5%
Verdict	Pass		





Page 14 of 31








6. Measurement of Electrostatic discharge

6.1. Requirements

Port	Enclosure
Basic Standard	IEC 61000-4-2
	±8.0 kV (Air Discharge)
Test Level	±4.0 kV (Contact Discharge)
	±4.0 kV (Indirect Discharge)
Required Performance Criterion	В
Time Between Each Discharge:	1 second
Number of Discharge for Each	10
Applied Voltage	10

6.2. Block Diagram of Test Setup





Page 16 of 31

6.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
ESD Simulator	Schaffner	NSG 438	782	Nov. 13, 2023	Nov. 12, 2024

Measuring Software

Software Name	Manufacturer	Details

6.4. Configuration of the EUT and method of measurement

- a. Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- b. The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- c. The time interval between two successive single discharges was at least 1 second.
- d. The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the EUT.
- e. Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- f. Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were completed.
- g. At least ten single discharges (in the most sensitive polarity) were applied to the Horizontal Coupling Plane at points on each side of the EUT. The ESD generator was positioned vertically at a distance of 0.1 meters from the EUT with the discharge electrode touching the HCP.
- h. At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the Vertical Coupling Plane in sufficiently different positions that the four faces of the EUT were completely illuminated. The VCP (dimensions 0.5m×0.5m) was placed vertically to and 0.1 meters from the EUT.
- i. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Page 17 of 31

6.5. Test Summary

Test Engineer	Carpe Lin	Temperature	21.5℃
Test Date	2024-09-08	Air Pressure	985 Mbar
Test Mode(s)	Mode 1	Relative Humidity	54.5%
Verdict	Pass		

Voltage	Coupling	Observation	Performance
±4kV	Contact Discharge	No degradation of performance	A
±2KV, ±4kV, ±8kV	Air Discharge	No degradation of performance	N/A
±4kV Indirect Discharge HCP		No degradation of performance	A
±4kV	Indirect Discharge VCP	No degradation of performance	А

Red line: Contact Discharge



Note: No Air Discharge



Page 18 of 31


7. Measurement of Radio-Frequency Electromagnetic Field

7.1. Requirements

Port	Enclosure
Basic Standard	IEC 61000-4-3
Required Performance Criterion	A
Test Level	3V/m with 80% AM. 1kHz Modulation at 80 to 1000MHz
Antenna polarization	Vertical and Horizontal
Step size increment ^a	1%
Dwell time ^b	≤5 seconds
Test Distance	3m
EUT position facing antenna	Front side, back side, left side and right side


Notes:

- a. Recognizing that a 1% step size is preferred, the frequency range can be swept incrementally with a step size not exceeding 4% of the previous frequency with a test level of twice the value of the specified test level in order to reduce the testing time for equipment requiring testing in multiple configurations and/or long cycle times.
- b. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to be able to respond. However, the dwell time shall not exceed 5 seconds at each of the frequencies during the scan. The time to exercise the EUT is not interpreted as a total time of a program or a cycle but related to the reaction time in case of failure of the EUT.





7.2. Block Diagram of Test Setup





Page 20 of 31

7.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Generator	Aglient	N5182A	MY50140530	Feb. 01, 2024	Jan. 31, 2025
Directional Couple	Werlatonee	C6026-10	99482	Feb. 01, 2024	Jan. 31, 2025
Directional Couple	Werlatonee	C5571-10	99463	Feb. 01, 2024	Jan. 31, 2025
Power Probe	R&S	URV5-Z4	100124	Mar. 24, 2023	Mar. 23, 2025
Power Meter	R&S	NRVD	8323781027	Mar. 24, 2023	Mar. 23, 2025
Power Amplifier	KALMUS	7100LC	04-02/17-06-001	Sep. 21, 2023	Sep. 20, 2024
Power Amplifier	Milmega	AS0104-55_55	1004793	Oct. 13, 2023	Oct. 12, 2024
Power Amplifier	Rflight	NTWPA-2560100	17063183	Oct. 13, 2023	Oct. 12, 2024
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00034609	Mar. 31, 2024	Mar. 30, 2025
Wideband Antenna	ETS-LINDGREN	3142C	00060447	N/A	N/A

Measuring Software

Software Name	Manufacturer	Details	
TS+[JS35-RS]	Tonscend	For EMC measurement, version 2.0.1.8	

7.4. Configuration of the EUT and method of measurement

- a. The Equipment Under Test (EUT) was positioned within the Uniform Field Area (UFA) on a supporting table, ensuring a 3-meter separation from the transmitting antenna. This setup aligns with the calibrated square area, guaranteeing field uniformity during testing. The supporting units were strategically located outside the UFA to avoid any potential interference. Nonetheless, the cables connected to the EUT were intentionally exposed to the precisely calibrated field within the UFA.
- b. Before testing, it will verify the proper operation of the test equipment/system. This verification will involve measuring the field strength at one point within the Uniform Field Area (UFA) at various frequencies.
- c. The test shall be performed according to the above requirements and block diagram which shall specify the test setup.
- d. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Page 21 of 31

7.5. Test Summary

Test Engineer	Carpe Lin	Temperature	22.8℃
Test Date	2024-09-07	Air Pressure	985 Mbar
Test Mode(s)	Mode 1	Relative Humidity	58.5%
Verdict	Pass		

Frequency	Exposed Side	Field Strength (V/m)	Observation	Performance
80MHz to 1GHz	Front	2) //m /mm a)	No degradation of performance	А
	Left		No degradation of performance	А
	Rear	3V/m (rms)	No degradation of performance	А
	Right		No degradation of performance	А




Page 22 of 31

8. Measurement of Power Frequency Magnetic Field

8.1. Requirements

Port	Enclosure
Basic Standard	IEC 61000-4-8
Test Level	3 A/m
Frequency	50 or 60 Hz
Required Performance Criterion	Α
Application of the magnetic field	Continuous

8.2. Block Diagram of Test Setup





Page 23 of 31

8.3. Equipment Details

Measuring Instruments

Instruments	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Power frequency field immunity	HTEC	HPFMF	161701	Apr. 30, 2024	Apr. 29, 2025
device with coil				, ,	, ,

Measuring Software

Software Name	Manufacturer	Details

8.4. Configuration of the EUT and method of measurement

- a. The test shall be performed according to the above requirements and block diagram which shall specify the test setup.
- b. The power supply, signal and other functional electrical quantities shall be applied within their rated range.
- c. If the actual operating signals are not available, they may be simulated.
- d. Preliminary verification of equipment performances shall be carried out prior to applying the test magnetic field.
- e. The plane of the inductive coil shall then be rotated by 90° in order to expose the EUT to the test field with different orientations and the same procedure.
- f. The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance criterion defined in the report.



Page 24 of 31


8.5. Test Summary

Test Engineer	Carpe Lin	Temperature	22.3℃
Test Date	2024-09-08	Air Pressure	985 Mbar
Test Mode(s)	Mode 1	Relative Humidity	52.9%
Verdict	Pass		

Frequency	Test Level	Observation	Performance
50Hz	3A/m	No degradation of performance	A
60Hz	3A/m	No degradation of performance	A




9. Photographs of Test Setup




Radiated emissions at frequencies up to 1 GHz



Electrostatic discharge







Radio-frequency electromagnetic field up to 1 GHz



Measurement of Power Frequency Magnetic Field




10. Photographs of EUT




Top view of EUT



Bottom view of EUT








Front view of EUT




Back view of EUT








Left view of EUT




Right view of EUT








Open view of EUT



Internal view-1 of EUT







Battery view of EUT ----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.