

Applicant: Mid Ocean Brands B.V.

Product: USB HUB

Trademark: N/A

Model No.: MO8930

Test Standards: EN 55032;2015+A11:2020+A1:2020

EN IEC 61000-3-2:2019 EN 55035:2017+A1:2020 EN 61000-3-3: 2013+A1:2019

Test Result:

The EMC testing has been performed on the submitted

samples and found in compliance with council EMC Directive

2014/30/EU.

Approved By

Terry Tang

Manager


Dated: February 07, 2023

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com



Report No.: TW2302048E Page 2 of 45

Date: 2023-02-07



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Date: 2023-02-07



TABLE OF CONTENT

Test Report Conclusion	
Special Statement	
Content	
General Details	5
Test Lab Details.	5
Applicant Details	5
Description of EUT	5
Submitted Sample.	6
Test Duration	6
Additional Information of EUT.	6
Test Engineer & Verify Engineer.	6
List of Measurement Equipment.	7
Conducted Emission Test.	7
Radiated Disturbance Test.	7
Harmonic& Flicker Test.	7
ESD Test	7
RF Field Strength Susceptibility.	8
Electrical Fast Transient/Burst (EFT/B) Immunity Test.	8
Surge Test.	8
Conducted Immunity Test.	8
Power-Frequency Magnetic Field.	8
Voltage Dips/Interruption Immunity Test	9
Technical Details	10
Investigations Requested.	10
Test Standards.	10
Performance Criteria.	10
Test Standards and Results Summary Tables.	11
Electromagnetic Interference Test Results.	12
Power line Conducted Emission Test.	12
Telecommunication Ports Conducted Emission Test.	15
Radiated Disturbance Test.	18
Harmonic Current Emission Test.	21
Voltage Fluctuations &Flicker Test.	23
	Special Statement Content General Details. Test Lab Details. Applicant Details. Description of EUT. Submitted Sample. Test Duration. Additional Information of EUT. Test Engineer & Verify Engineer. List of Measurement Equipment Conducted Emission Test. Radiated Disturbance Test. Harmonic& Flicker Test. ESD Test RF Field Strength Susceptibility. Electrical Fast Transient/Burst (EFT/B) Immunity Test. Surge Test. Conducted Immunity Test. Power-Frequency Magnetic Field. Voltage Dips/Interruption Immunity Test. Technical Details. Investigations Requested. Test Standards. Performance Criteria. Test Standards and Results Summary Tables. Electromagnetic Interference Test Results. Power line Conducted Emission Test. Radiated Disturbance Test. Harmonic Current Emission Test.

5.0

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Immunity Test

adopt any other remedies which may be appropriate.

Page 4 of 45

Report No.: TW2302048E

Date: 2023-02-07



5.1	Electrostatic Discharge.	24
5.2	RF Field transients / Burst Immunity Test.	26
5.3	Electrical Fast Transient/Burst (EFT/B) immunity test.	28
5.4	Surge Test.	30
5.5	Conducted Immunity Test.	32
5.6	Power-Frequency Magnetic Field.	34
5.7	Voltage Dips / Interruptions Immunity Test.	36
<u>6.0</u>	Product Labeling	38
6.1	CE Mark label specification.	38
	Appendix	39

Date: 2023-02-07



1.0 General Details

1.1 Test Lab Details

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan

Page 5 of 45

District, Shenzhen, China

Tel: +86 755 83448688 Fax :+86 755 83442996

Test Location

All tests were performed at:

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan

District, Shenzhen, China

Tel: +86 755 83448688 Fax: +86 755 83442996

1.2 Applicant Details

Applicant: Mid Ocean Brands B.V.

Address: 7/F., Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong.

Telephone: -Fax: --

Manufacturer: Mid Ocean Brands B.V.

Address: 7/F., Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong.

Telephone: -Fax: --

1.3 Description of EUT

Product: USB HUB

Trademark: N/A

Model Number: MO8930

Adding Trademark: N/A

Adding Model Number: N/A

Rating: --

Note: This is an addition test report based on original one: TW2103092E. The applicant address and Product names are changed.

The report refers only to the sample tested and does not apply to the bulk.



Date: 2023-02-07



1.4 Submitted Sample(s)

1 Samples

1.5 Test Duration

1.7

Date of Receipt of Application: March 09, 2021 Date of Test: March 09, 2021 ~ February 07, 2023

1.6 Additional information of EUT

	Submitted	Not Available
User Manual	\boxtimes	
Part List		
Circuit Diagram	\boxtimes	
Printed circuit board[PCB]	\boxtimes	
Layout		
Block Diagram		
Test Engineer		_
	Pa	is. Lon
The sample(s) tested by	FC	N. Fun

This test report is not valid without personnel's signatures of SHENZHEN TIMEWAY TESTING LABORATORIES.

Print Name: Leo Lau/ Engineer

Date: 2023-02-07



2.0 List of Measurement Equipment

2.1 Conducted Emission Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESCS 30	834115/006	RS	2022.07.15	1Year
LISN	NNB42	00012	SCHAFFNER	2022.08.18	1Year

2.2 Radiated Disturbance Test

				Calibration	Calibration
Name	Model No	Serial No.	Manufacturer	Date	Cycle
EMI Test Receiver	ESPI 3	100379	RS	2022.07.15	1Year
Spectrum Analyzer	E4407B	MY50441392	HP/Agilent	2022.07.15	1Year
Amplifier	BBV9743	#218	HP/Agilent	2022.07.15	1Year
Bilog Antenna	VULB9163	9163/340	Schwarebeck	2022.07.18	3Year
Horn Antenna	BBHA 9120D	9120D-631	RS	2022.07.18	3Year
Amplifier	8449B	3008A00160	HP/Agilent	2022.07.15	1Year

2.3 Harmonic & Flicker Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
Harmonics Flicker Test					
System	PACS-1	72305	CI	2022.07.15	1Year
5K VA AC Power					
Source	5001iX	56060	CI	2022.07.15	N/A

2.4 ESD Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
ESD Simulator	DITO	0404-24	EM TEST	2022.07.18	1Year

2.5 RF field Strength Susceptibility

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
Signal Generator	SMT03	100059	RS	2022.07.15	1Year
Power Meter	NRVS		RS	2022.07.15	1Year
Voltage Probe	URV5-Z2	100012	RS	2022.07.15	1Year

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2023-02-07



Voltage Probe	URV5-Z2	100013	RS	2022.07.15	1Year
Power Amplifier	150W1000	300999	AR	2022.07.15	1Year
Power Amplifier	25S1G4AM1	305993	AR	2022.07.15	1Year
Field Probe	CBL6111C	2576	Holaday	2022.07.15	1Year
Bilog Antenna	MCDC		Chase	2022.07.15	1Year

2.6 Electrical Fast Transient/Burst (EFT/B) Immunity test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
EFT Generator	UCS 500 M4	0304-42	EM TEST	2022.07.15	1Year
Power Source	MV2616	0104-14	EM TEST	2022.07.15	1Year

2.7 Surge Test

					Calibration
Name	Model No.	Serial No.	Manufacturer	Calibration Date	Cycle
Ultra Compact	UCS 500				
Simulator	M4	0304-42	EM TEST	2022.07.15	1Year
Power Source	MV2616	0104-14	EM TEST	2022.07.15	1Year

2.8 Conducted Immunity Test

					Calibration	Calibration
Name		Model No.	Serial No.	Manufacturer	Date	Cycle
Continuous	Wave					
Simulator		CWS 500C	0407-05	EM TEST	2022.07.15	1 Year

2.9 Power-frequency Magnetic Field

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
Continuous Wave					
Simulator	UCS 500 M4	0304-42	EM TEST	2022.07.15	1 Year
Power Source					
Network	MV 2616	0104-14	EM TEST	2022.07.15	1 Year
Current Transformer	MC2630		EM TEST	2022.07.15	1 Year
Magnetic Coil	MS100	0304-42	EM TEST	2022.07.15	1 Year

Page 9 of 45 Report No.: TW2302048E

Date: 2023-02-07



2.10 Voltage Dips/Interruption Immunity Test

				Calibration	Calibration
Name	Model No.	Serial No.	Manufacturer	Date	Cycle
Ultra Compact					
Simulator	UCS 500 M4	0304-42	EM TEST	2022.07.15	1Year
Power Source	MV2616	0104-14	EM TEST	2022.07.15	1Year

Report No.: TW2302048E Page 10 of 45

Date: 2023-02-07



3.0 Technical Details

3.1 Investigations Requested

Perform Electromagnetic Interference [EMI] & Electromagnetic Susceptibility [EMS] tests for CE Marking

3.2 Test Standards

	Test Standards						
EN 55032:2015+A11:2020+A1:2020	Electromagnetic compatibili Requirements	Electromagnetic compatibility of multimedia equipment - Emission Requirements					
EN IEC 61000-3-2:2019+ A1:2021	Electromagnetic compatibility(EMC)- Part 3-2:Limits-Limits for harmonic current emissions(equipment input current ≤ 16A per phase)						
EN 61000-3-3:2013 +A2:2021+AC:2022	Electromagnetic compatibility (EMC)- Part 3-3:Limits-Limitation of voltage changes, Voltage fluctuations and flicker in public low-voltage supply systems. For equipment with rated current ≤ 16A per phase and not subject to conditional connection						
EN 55035:2017+A11:2020	Electromagnetic compatibili requirements	ty of multimedia equipment - Immunity					
	EN 61000-4-2:2009	Electrostatic discharge					
	EN IEC 61000-4-3:2020	RF electromagnetic field disturbances					
	EN 61000-4-4:2012	Electrical Fast transients					
	EN 61000-4-5:2014	Surge					
	EN 61000-4-6:2014 Conducted susceptibility						
	EN 61000-4-8:2010	Power-frequency Magnetic Field					
	EN IEC 61000-4-11: 2020	Dips/Voltage Interruption Variation					

3.3 Performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Page 11 of 45 Report No.: TW2302048E

Date: 2023-02-07



3.4 **Test standards and Results Summary Tables**

Test Condition	Test Requirement	Test Method	Test Result			
EMISSION Results Summary						
Conducted Emission on AC	EN 55032:2015	EN 55032:2015	Dogg			
Mains, 150kHz to 30MHz	+A11:2020+A1:2020	+A11:2020+A1:2020	Pass			
Conducted Emission on at	EN 55032:2015	EN 55032:2015				
telecommunication ports,	+A11:2020+A1:2020	+A11:2020+A1:2020	N/A			
150kHz to 30MHz						
Radiated Emissions,	EN 55032:2015	EN 55032:2015	Pass			
30MHz to 6GHz	+A11:2020+A1:2020	+A11:2020+A1:2020	Pass			
Harmonic Emissions on AC	EN IEC 61000-3-2:2019	EN IEC 61000-3-2:2019	N/A			
supply	+A1:2021	+A1:2021	N/A			
Voltage fluctuations on AC	EN 61000-3-3:2013	EN 61000-3-3:2013	N/A			
supply	+A2:2021+AC:2022	+A2:2021+AC:2022	IN/A			
	IMMUNITY Results Sumn	nary				
Electrostatic Discharge	EN 55035:2017+A11:2020	EN 61000-4-2: 2009	Pass			
Continuous RF electromagnetic	EN 55035:2017+A11:2020	EN IEC 61000-4-3:2020	Pass			
field disturbances			1 ass			
Continuous induced RF	EN 55035:2017+A11:2020	EN 61000-4-6:2014	Pass			
disturbances						
Power frequency magnetic field	EN 55035:2017+A11:2020	EN 61000-4-8: 2010	N/A			
Electrical fast transients/burst	EN 55035:2017+A11:2020	EN 61000-4-4: 2012	Pass			
(EFT/B)						
Surges	EN 55035:2017+A11:2020	EN 61000-4-5: 2014	Pass			
Voltage dips and interruptions	EN 55035:2017+A11:2020	EN IEC 61000-4-11: 2020	Pass			
Broadband impulsive conducted disturbances	EN 55035:2017+A11:2020	EN 61000-4-6:2014	N/A			

Note: N/A-Not applicable


Date: 2023-02-07



4.0 Electromagnetic Interference Test results

4.1 Power line Conducted Emission Test


4.1.1 Schematics of the test



4.1.2 Test Method:

The test was performed in accordance with EN 55032:2015+A11:2020+A1:2020

Block diagram of Test setup



4.1.3 Power line conducted Emission Limit

	Limits dB(μ V)					
Frequency(MHz)	Class A l	Class A Equipment		quipment		
	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0		
5.00 ~ 30.00	73.0	60.0	60.0	50.0		

Notes: 1. *decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies

4.1.4 Test Results

Limits for Conducted Emission test, Please refer to limit line (Quasi-peak)and Average in the following diagram labelled as (QP)&AV

Remark: Calculated measurement uncertainty=3.6dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2023-02-07



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: WORKING

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1890	38.51	9.76	48.27	64.08	-15.81	QP	Р
2	0.1890	17.53	9.76	27.29	54.08	-26.79	AVG	Р
3	0.2319	33.19	9.75	42.94	62.38	-19.44	QP	Р
4	0.2319	15.22	9.75	24.97	52.38	-27.41	AVG	Р
5	0.2982	25.16	9.76	34.92	60.29	-25.37	QP	Р
6	0.2982	7.79	9.76	17.55	50.29	-32.74	AVG	Р
7	0.4854	15.91	9.77	25.68	56.25	-30.57	QP	Р
8	0.4854	5.77	9.77	15.54	46.25	-30.71	AVG	Р
9	19.0641	39.98	10.62	50.60	60.00	-9.40	QP	Р
10	19.0641	32.32	10.62	42.94	50.00	-7.06	AVG	Р

Date: 2023-02-07



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: WORKING

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1655	39.18	9.77	48.95	65.18	-16.23	QP	Р
2	0.1655	17.23	9.77	27.00	55.18	-28.18	AVG	Р
3	0.1929	37.87	9.75	47.62	63.91	-16.29	QP	Р
4	0.1929	14.75	9.75	24.50	53.91	-29.41	AVG	Р
5	0.2475	33.19	9.75	42.94	61.84	-18.90	QP	Р
6	0.2475	13.28	9.75	23.03	51.84	-28.81	AVG	Р
7	4.6458	16.69	9.91	26.60	56.00	-29.40	QP	Р
8	4.6458	10.57	9.91	20.48	46.00	-25.52	AVG	Р
9	19.3257	38.98	10.64	49.62	60.00	-10.38	QP	Р
10	19.3257	30.90	10.64	41.54	50.00	-8.46	AVG	Р

Date: 2023-02-07



4.2 Telecommunication ports Conducted Emission Test

4.2.1 Schematics of the test




EUT: Equipment Under Test

4.2.2 Test Method:

The test was performed in accordance with EN 55032:2015+A11:2020+A1:2020

Block diagram of Test setup



4.2.3 Telecommunication ports conducted Emission Limit

	Class A Limits				Class B Limits			
Frequency(MHz)	Quasi-pe	i-peak Level Average Level		Quasi-peak Level		Average Level		
rrequency(WHIZ)	Vlotage	Current	Vlotage	Current	Vlotage	Current	Vlotage	Current
	dB(uV)	dB(uA)	dB(uV)	dB(uA)	dB(uV)	dB(uA)	dB(uV)	dB(uA)
$0.15 \sim 0.50$	97 to 87	53 to43	84 to74	40 to 30	84 to 74	40 to30	74 to64	30 to 20
0.50 ~ 30.00	87	43	74	30	74	30	64	20

Notes:

- 1. *decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

4.2.4 Test Results: N/A

Limits for Conducted Emission test, Please refer to limit line (Quasi-peak)and Average in the following diagram labelled as (QP)&AV

Remark:

Calculated measurement uncertainty=1.9dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2302048E Page 16 of 45

Date: 2023-02-07



Conducted Emission on Telecommunication port (150kHz to 30MHz) A:

EUT Operating Environment

Temperature: 25°C Humidity: 75 %RH Atmospheric Pressure: 101 kPa

EUT set Condition: Normal operation mode

Equipment Level: Class B

Results: N/A

Please refer to following diagram for individual

Frequency	Dort	Port Reading(dBµV)		Limit(dBµV)	
(MHz)	FOIL	Quasi-peak	Average	Quasi-peak	Average

Report No.: TW2302048E Page 17 of 45

Date: 2023-02-07



B: Conducted Emission on Telecommunication port (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 75 %RH Atmospheric Pressure: 101 kPa

EUT set Condition: Normal operation mode

Equipment Level: Class B

Results: N/A

Please refer to following diagram for individual

Frequency	Port	Reading(dBμA)		Limit(dBµA)	
(MHz)	FOIL	Quasi-peak	Average	Quasi-peak	Average

Note: This test item is not applicable because there is no telecommunication port

Date: 2023-02-07



4.3 Radiated Disturbance Test


4.3.1 Schematics of the test



4.3.2 Test Method:

The test was performed in accordance with EN 55032:2015+A11:2020+A1:2020

Block diagram of Test setup



4.3.3 Radiated Disturbance Test Limit

Frequency Range (MHz)	Quasi-Peak limits (dB µ V/m)		
	Class A Limits	Class B Limits	
3 -230	50.00	40.00	
230-1000	57.00	47.00	
1000-3000	56(AV)/76(PK)	50(AV)/70(PK)	
3000-6000	60(AV)/80(PK)	54(AV)/74(PK)	

Note: The lower limit shall apply at the transition frequencies

4.3.4 Test result

Limits for Radiated Disturbance test, Please refer to limit line (Quasi-peak) in the following diagram labelled as (QP)

Remark:

Calculated measurement uncertainty=4.7dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2023-02-07



A: Radiated Disturbance (30MHz----1000MHz)


Project Number: CASE4 Test Time: 2021-03-22_10.29.14

EUT Name: USB HUB Test Engineer: HAVEN

Manufacturer: Mid Ocean Brands B.V Test Standard: EN 55032

Model: MO8930 Work Addition: WORKING

Temp.(oC): 25 Load: Hum.: 65% Remark:



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	202.752	40.46	-13.40	40.0	0.46	Peak	28.00	120	Horizontal	N/A
1*	202.752	36.49	-13.40	40.0	-3.51	QP	28.00	120	Horizontal	Pass
2	254.741	37.45	-11.92	47.0	-9.55	Peak	274.00	100	Horizontal	Pass
3	303.472	31.65	-10.99	47.0	-15.35	Peak	20.00	100	Horizontal	Pass
4	332.322	30.44	-10.10	47.0	-16.56	Peak	356.00	100	Horizontal	Pass
5	899.873	40.02	-1.85	47.0	-6.98	Peak	312.00	100	Horizontal	Pass
6	960.256	45.67	-1.63	47.0	-1.33	Peak	340.00	149	Horizontal	Pass
6*	960.256	42.70	-1.63	47.0	-4.30	QP	340.00	149	Horizontal	Pass

Date: 2023-02-07



B: Radiated Disturbance (30MHz----1000MHz)

Project Number: CASE4 Test Time: 2021-03-22_10.30.46


EUT Name: USB HUB Test Engineer: HAVEN

Manufacturer: Mid Ocean Brands B.V Test Standard: EN 55032

Model: MO8930 Work Addition: WORKING

 Temp.(oC):
 25
 Load:

 Hum.:
 65%
 Remark:



No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
1	67.578	25.65	-14.47	40.0	-14.35	Peak	286.00	100	Vertical	Pass
2	202.617	25.90	-13.40	40.0	-14.10	Peak	17.00	100	Vertical	Pass
3	249.893	27.90	-12.08	47.0	-19.10	Peak	57.00	100	Vertical	Pass
4	720.225	31.62	-4.04	47.0	-15.38	Peak	45.00	100	Vertical	Pass
5	764.349	34.48	-3.25	47.0	-12.52	Peak	51.00	100	Vertical	Pass
6	960.240	35.12	-1.63	47.0	-11.88	Peak	113.00	100	Vertical	Pass

Page 21 of 45


Report No.: TW2302048E

Date: 2023-02-07



4.4 Harmonic Current Emission Test

4.4.1 Schematic of the test




EUT: Equipment Under Test

4.4.2 Test Method:

The test was performed in accordance with EN IEC 61000-3-2:2019 +A1:2021

*: The Level of the product is : CLASS D

Block diagram of Test setup



4.4.3 Limits of Harmonic Current Emission For Class A

Date: 2023-02-07



Harmonic order	Maximum permissible harmonic current				
n	A				
Odd harmonics					
3	2,30				
5	1,14				
7	0,77				
9	0,40				
11	0,33				
13	0,21				
15 ≤ n ≤ 39	0,15 <u>15</u>				
Even har	monics				
2	1,08				
4	0,43				
6	0,30				
8 ≤ n ≤ 40	0,23 <u>8</u>				

4.4.4 Test Results

Please refer to the following pages

Harmonic Current Emission Test

EUT Operating Environment

Humidity: 53%RH Temperature: 25°C Atmospheric Pressure: 101 kPa

EUT set Condition:

Results: N/A

N/A --- DC Operation.

Please refer to following diagram for individual

Harmonic results as a% of the limits

No	(Test	No	(Test	No	(Test	No	(Test
	result/Limit)%		res lt/Limit)%		result/Limit)%		result/Limit)%
1		11		21		31	
2		12		22		32	
3		13		23		33	
4		14		24		34	
5		15		25		35	
6		16		26		36	
7		17		27		37	
8		18		28		38	
9		19		29		39	
10		20		30		40	_

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No.: TW2302048E Page 23 of 45

Date: 2023-02-07



4.5 <u>Voltage Fluctuations & Flicker Test</u>

4.5.1 Schematic of the test




EUT: Equipment Under Test

4.5.2 Test Method:

The test was performed in accordance with EN 61000-3-3:2013+A2:2021+AC:2022

Block diagram of Test setup




4.5.3 Test Results

Result: N/A

Date: 2023-02-07



- 5.0 Immunity Test
- 5.1 Electrostatic Discharge
- 5.1.1 Schematic of the test



5.1.2 Test method

The test was performed in accordance with EN 61000-4-2: 2009

5.1.3 Test severity

±4kV for direct & in-direct Contact Discharge

 $\pm 8kV$ for air Discharge

Performance Criterion Require: **B** (Please see following table)

5.1.4 Susceptibility performance Criteria and Severity level

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Level	Test Voltage Direct & in-direct contact	Test Voltage Air
	Discharge (kV)	discharge(kV)
1	$\pm 2 \mathrm{kV}$	±2kV
2	$\pm 4 \mathrm{kV}$	$\pm 4 \mathrm{kV}$
3	$\pm6\mathrm{kV}$	$\pm 8 \mathrm{kV}$
4	$\pm8\mathrm{kV}$	±15kV

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2302048E Page 25 of 45

Date: 2023-02-07



5.1.5 Test Result

EUT Operating Environment

Temperature: 25 °C Humidity: 53%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Location	Discharge Method	Test Voltage	Results
HCP (Horizontal coupling plane)	In-Direct	$\pm 2kV, \pm 4kV$	Pass
VCP (Vertical Coupling plane)	In-Direct	$\pm 2kV, \pm 4kV$	Pass
USB Port	Contact Discharge	$\pm 2kV, \pm 4kV$	Pass
Enclosure	Air Discharge	$\pm 2kV, \pm 4kV, \pm 8kV$	Pass

Remark: Calculated measurement uncertainty= 0.2kV

Date: 2023-02-07



5.2 RF field strength susceptibility (80MHz-1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz)

5.2.1 Schematics of the test



EUT: Equipment Under Test

5.2.2 Test Method:

Modulation:


The test was performed in accordance with EN IEC 61000-4-3:2020

Severity: Level 2 (3V/m)

80% AM

Performance Criterion Require: A (Please see following table)

Block diagram of Test setup



5.2.3 Susceptibility performance Criteria and severity Level

Susceptibility performance Criteria

Criterion	Description			
A	A No change in operational mode or degradation of performance outside of specification and no change in stored parameters.			
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.			
C Loss of function allowed during the test, provided that function is selection recoverable or can be recovered by operation of controls.				

Severity Level

Level	Field Strength (V/m)
1	1
2	3
3	10

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2302048E Page 27 of 45

Date: 2023-02-07



5.2.4 Test Result:

EUT Operating Environment

Temperature: 25 °C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Frequency	Face	Polarity	Level	Dwell	Sweep	Results
(MHz)			(V/m)	Time(s)	Rate (%)	
80-1000	0°	Horizontal	3	1	1	Pass
80-1000	90°	Horizontal	3	1	1	Pass
80-1000	180°	Horizontal	3	1	1	Pass
80-1000	270°	Horizontal	3	1	1	Pass
80-1000	0°	Vertical	3	1	1	Pass
80-1000	90°	Vertical	3	1	1	Pass
80-1000	180°	Vertical	3	1	1	Pass
80-1000	270°	Vertical	3	1	1	Pass
1800,	0°	Horizontal	3	1	1	Pass
2600,	90°	Horizontal	3	1	1	Pass
3500,	180°	Horizontal	3	1	1	Pass
5000	270°	Horizontal	3	1	1	Pass
1800,	0°	Vertical	3	1	1	Pass
2600,	90°	Vertical	3	1	1	Pass
3500,	180°	Vertical	3	1	1	Pass
5000	270°	Vertical	3	1	1	Pass

Date: 2023-02-07



5.3 Electrical Fast Transient/Burst (EFT/B) immunity test

5.3.1 Schematics of the test




5.3.2 Test Method

The test was performed in accordance with EN 61000-4-4:2012

Severity: Level 2 (1kV)

Performance Criterion Require: **B** (Please see following table)

Block diagram of Test setup



5.3.3 Susceptibility performance Criteria and Severity Level

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

	Open Circuit output Test Voltag	ge ±10%
Level	On power Supply Lines	On I/O (Input/output)
		Signal data and control lines
1	0.5kV	0.5kV
2	1kV	1kV
3	2kV	2kV
4	4kV	4kV
X	Special	Special

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2302048E Page 29 of 45

Date: 2023-02-07



5.3.4 Test Results

EUT Operating Environment

Temperature: 25 °C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Inject location: AC mains

Inject Line	Voltage	Inject	Method	Results
	kV	Times (s)		
L	±1	120	Direct	Pass
N	±1	120	Direct	Pass
L-N	±1	120	Direct	Pass

Page 30 of 45

Report No.: TW2302048E

Date: 2023-02-07



5.4 Surge test

5.4.1 Schematics of the test




5.4.2 Test Method:

The test was performed in accordance with EN 61000-4-5:2014

Severity: Level 2 (Line to Neutral at 1kV)

Performance Criterion Require: B (Please see following table)

Block diagram of Test setup



5.4.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Report No.: TW2302048E Page 31 of 45

Date: 2023-02-07



Severity Level

Severity Level	Open-Circuit Test Voltage	
	kV	
1	0.5	
2	1.0	
3	2.0	
4	4.0	
*	Special	

5.4.4 Test Results

EUT Operating Environment

Humidity: 75%RH Atmospheric Pressure: 101 kPa Temperature: 25°C

Please refer to the following table for individual results.

Test location:


Location	Polarity	Phase	No of	Pulse	Results
		Angle	Pulse	Voltage(kV)	
LN	<u>±</u>	0	5	1.0	Pass
	<u>±</u>	90	5	1.0	Pass
L-N	<u>±</u>	180	5	1.0	Pass
	<u>±</u>	270	5	1.0	Pass

Date: 2023-02-07



5.5 Conducted Immunity test

5.5.1 Schematics of the test




5.5.2 Test Method

The test was performed in accordance with EN 61000-4-6:2014

Severity: Level 2 (3 V rms),0.15MHz—80MHz

Performance Criterion Require: A (Please see following table)

Block diagram of Test setup



5.5.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Severity Level	Voltage Level (e.m.f) V
1	1
2	3
3	10
*	Special

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2302048E Page 33 of 45

Date: 2023-02-07



5.5.4 Test Results:

EUT Operating Environment

Temperature: 25 °C Humidity: 75%RH Atmospheric Pressure: 101 KPa

Please refer to the following table for individual results.

Frequency	Injected Position	Strength	Criterion	Result
Range (MHz)				
0.15 - 10	AC Line	3V (rms)	A	Pass
10 - 30	AC Line	3 to 1V (rms)	A	Pass
30-80	AC Line	1V (rms)	A	Pass

Note: the amplitude of a test level varies over a given frequency range, it changes linearly with respect to the logarithm of the frequency

Date: 2023-02-07



5.6 Power-Frequency magnetic field test

5.6.1 Schematics of the test




5.6.2 Test Method

The test was performed in accordance with EN 61000-4-8:2010

Severity: Level 1 (1A/m),

Performance Criterion Require: A (Please see following table)

Block diagram of Test setup



5.6.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Severity Level	Magnetic Field Strength A/m
1	1
2	3
3	10
4	30
5	100
*	Special

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2302048E Page 35 of 45

Date: 2023-02-07



5.6.4 Test Results:

EUT Operating Environment

Temperature: 25 °C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Test Level	Testing Duration	Coil Orientation	Criterion	Result
1A/m	5 Mins	X	A	N/A
1A/m	5 Mins	Y	A	N/A
1A/m	5 Mins	Z	A	N/A

Page 36 of 45

Report No.: TW2302048E

Date: 2023-02-07



5.7 Voltage Dips/Interruptions immunity test


5.7.1 Schematics of the test



5.7.2 Test Method:

The test was performed in accordance with EN IEC 61000-4-11: 2020 Performance Criterion Require: C&B (Please see following table)

Block diagram of Test setup



5.7.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
В	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Report No.: TW2302048E Page 37 of 45

Date: 2023-02-07



Severity Level

	Test Level %Ut	Reduction	Duration	Performance		
Voltage			(Periods)	Criteria		
Dip	<5	>95	0.5	В		
	70	30	25	С		
	·					
Walters	Test Level %Ut	Reduction	Duration	Performance		
Voltage Interceptions			(Periods)	Criteria		
	<5	>95	250	C		

5.7.4 Test Result:

EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Voltage Dip:

Test Level	Reduction	Duration	Phase Angle	Meet	Result
% Ut		(periods)		Criterion	
0	100	0.5	0° -360°	В	Pass
70	30	25	0° -360°	С	Pass

Voltage Interceptions:

Test Level % Ut	Reduction	Duration (periods)	Phase Angle	Meet Criterion	Result
0	100	250	0° - 360°	С	Pass

Report No.: TW2302048E Page 38 of 45

Date: 2023-02-07



6.0 Product Labelling

6.1 CE Mark label specification

Text of the mark is black or white in color and is left justified. Labels are printed in indelible ink on permanent adhesive backing and shall be affixed at a conspicuous location on the EUT or silk-screened onto the EUT.



6.2 Mark Location: Rear enclosure

Date: 2023-02-07



Appendix:

Conducted Emissions

Page 39 of 45



Report No.: TW2302048E Page 40 of 45

Date: 2023-02-07




Radiated Emissions



Date: 2023-02-07








Date: 2023-02-07








Date: 2023-02-07








Report No.: TW2302048E Page 44 of 45

Date: 2023-02-07





Report No.: TW2302048E Page 45 of 45

Date: 2023-02-07





-End of the report-